

P2

1FT±3%

P1

PIN OUT		
P1	568B Color	P2
1	White/Orange	1
2	Orange	2
3	White/Green	3
4	Blue	4
5	White/Blue	5
6	Green	6
7	White/Brown	7
8	Brown	8

Jacket

Bare Copper

Insulation

5.2mm

1, 2, 3, 4

1	2	3	4
BLU WH/BLU	ORG WH/ORG	GRN WH/GRN	BWN WH/BWN

A diagram of a 1000BASE-SX OM3 optical cable. The cable is shown in a circular loop, with two LC duplex connectors at the ends. The connectors are labeled 'LC' and 'Duplex'. The cable is labeled '1000BASE-SX OM3'.

300 cables per carton

Material:

- 4X2, 24AWG, twisted pair, 7*0.19±0.15MM
- OD: 5.2MM±0.30MM
- Insulation: HDPE-8380
- Jacket: PVC
- Contact Plug: UTP RJ45, 50μ"
- 568B Color wire standard
- Molded snaglass boot with strain relief
- Spot length on boot
- Connection 1:1

Scale	1:1							Name
TOLERANCE						Drawn	12.13.11	Chappel
X.X	±0.40					Approved		
X.XX	±0.25							
X.XXX	±0.15							
Angle	±3°					 		
			Modification	Date	Name			

Item No.	Item Description	Unit	Quantity	Unit Price	Total Price
----------	------------------	------	----------	------------	-------------

DK-1511-001/BL

Title	Cat 5e Patch Cord - Unshielded, Booted, UTP, 24AWG, Contact Plating 50μ" of Gold, Black, 1 Foot
--------------	---

Drawing No.

rev00

Replace

Sheet

RoHS Complaint

ASSMANN
VVS components