

For more Information
please call

1-800-Belden1



General Description:

12 AWG solid .086" bare copper conductor, foam FEP insulation, Duobond IV® quad shield (100% coverage), fluorocopolymer jacket.

Usage (Overall)

Suitable Applications: Thick Ethernet

Physical Characteristics (Overall)

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (mm)
1	12	Solid	BC - Bare Copper	2.1844

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
FFEP - Foam Fluorinated Ethylene Propylene	6.223

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	90
3	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
4		Braid	TC - Tinned Copper	90

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVDF - Fluorocopolymer

Overall Cable

Overall Nominal Diameter: 9.525 mm

Mechanical Characteristics (Overall)

Operating Temperature Range: -25°C To +150°C

UL Temperature Rating: 150°C

Bulk Cable Weight: 186.025 Kg/Km

Max. Recommended Pulling Tension: 1134.291 N

Min. Bend Radius/Minor Axis: 95.250 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification: CL2P, CMP

CEC/C(UL) Specification: CMP

89880 Coax - Coaxial Cable - Thicknet 10Base5 Ethernet

EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	IEEE802.3 10Base5
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-00324-00

Flame Test

UL Flame Test:	NFPA 262
CSA Flame Test:	FT6

Suitability

Suitability - Outdoor:	Yes
Suitability - Burial:	Yes

Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	9880

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
50	+/- 2

Nom. Inductance:

Inductance (μH/m)
0.211625

Nom. Capacitance Conductor to Shield:

Capacitance (pF/m)
85.306

Nominal Velocity of Propagation:

VP (%)
78

Nominal Delay:

Delay (ns/m)
4.2653

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
4.65902

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
4.98712

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100m)
1	0.59058
5	.37 max
10	.52 max
50	3.77315

METRIC MEASUREMENT VERSION

89880 Coax - Coaxial Cable - Thicknet 10Base5 Ethernet

100	5.41365
200	8.03845
400	12.4678
700	18.3736
900	22.3108
1000	23.6232

Max. Power Rating:

Freq. (MHz)	Rating (W)
1	15900
5	6928
10	4802
50	1992
100	1344
200	900
400	602
700	438
900	382
1000	361

Max. Operating Voltage - UL:

Voltage
300 V RMS

Notes (Overall)

Notes: Ring-band stripes every 2.5 meters to aid users in tap placement.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
89880 0031000	305 MT	60.782 KG	ORANGE	C	#11H FFEP SH SOL COAX
89880 0031640	500 MT	101.914 KG	ORANGE	C Z	#11H FFEP SH SOL COAX

Notes:

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND(+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 3 Revision Date: 09-25-2012

© 2014 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.