

8018 Hook-up/Lead - Aluminum Ground Wire

	For more information please call 1-800-Belden1 <u>See Put-ups and Colors</u>
---	---

Description:

8 AWG solid, soft annealed aluminum. Packaged in ten 50-foot connected coils or spools of 500 feet. Spools are marked every 100 feet for easy measuring.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1
Total Number of Conductors	1
AWG	8
Stranding	Solid
Conductor Material	Soft Annealed Aluminum

OVERALL:

Overall Nominal Diameter	.128 in.
--------------------------	----------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Conductor DC Resistance @ 20 Deg. C	1.03 Ohms/1000 ft
--	-------------------

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8018 00050	8 SOL ALUM GROUND WIRE	50	0.85	NONE	Q
8018 000500	8 SOL ALUM GROUND WIRE	500	8.5	NONE	

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 1 Revision Date: 10-02-2002

8018 Hook-up/Lead - Aluminum Ground Wire

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.