



Product: <u>83322E</u> ☑

Electronic, 2 C #16 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

Product Description

High Temperature Electronic, 2 Conductor 16AWG (19x29) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Physical Characteristics (Overall)

Conductor			
AWG	Stranding	Material	No. of Conductors
16	19x29	SC - Silvered Copper	2
Condu	ctor Count:		2
Total N	Number of Pa	airs:	1

Insulation

Material	Material Trade Name	Nominal Wall Thickness
PTFE - Polytetrafluoroethylene	Teflon®	0.011 in

Color Chart

Number	Color
1	White
2	Black

Outer Shield Material

Type	Material	Coverage [%]
Braid	SC - Silvered Copper	85 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
PTFE - Polytetrafluoroethylene	Teflon®	0.197 in	0.011 in

Construction and Dimensions

Cabling

Lay Direction	Twists
Left Hand	6 twist/ft

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
4.4 Ohm/1000ft	4.4 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
36 pF/ft	60 pF/ft

Inductance

Nominal Inductance 0.155 µH/ft

Current

Element	Max. Recommended Current [A]
35C Temperature Rise	11 Amps per conductor @ 25°C ambient

Voltage

Non-UL Voltage Rating 600 V RMS

Temperature Range

Operating Temp Range:	-65°C To +200°C	
-----------------------	-----------------	--

Mechanical Characteristics

Bulk Cable Weight:	33 lbs/1000ft
Max Recommended Pulling Tension:	95.5 lbs
Min Bend Radius/Minor Axis:	2 in

Standards

CPR Euroclass:	Eca
Military Specification:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
Other Specification:	NEMA HP3

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes	
EU Directive 2003/96/EC (BFR):	Yes	
EU Directive 2011/65/EU (ROHS II):	Yes	
EU Directive 2012/19/EU (WEEE):	Yes	
EU Directive 2015/863/EU:	Yes	
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)	
EU CE Mark:	Yes	
EU RoHS Compliance Date (yyyy-mm-dd):	: 2005-01-01	
MII Order #39 (China RoHS):	Yes	

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No	

Part Number

Variants

	Item #	Color	Putup Type	Length	UPC
	83322E 009100	White	Reel	100 ft	612825204084
	83322E 0091000	White	Reel	1,000 ft	612825204091
ı	83322E 009500	White	Reel	500 ft	612825204107

Footnote: E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.

Product Notes

Notes:	Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

History

Update and Revision:

Revision Number: 0.297 Revision Date: 04-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.