



**Product: 8459** ☑

Electronic, 25 C #22 Str TC, PVC Ins, PVC Jkt, CMG

# Request Sample

# **Product Description**

Electronic, 25 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, PVC Outer Jacket, CMG

## **Technical Specifications**

### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

## **Physical Characteristics (Overall)**

#### Conductor

Element	AWG	Stranding	N	Material	No. of Conductors
Conductor(s)	22	7x30	TC - Ti	inned Copper	25
Conductor Count:			25		

### Insulation

Element	Material	Nominal Wall Thickness
Conductor(s)	PVC - Polyvinyl Chloride	0.011 in

#### **Color Chart**

Color
Black
White
Red
Green
Orange
Blue
White/Black
Red/Black
Green/Black
Orange/Black
Blue/Black
Black/White
Red/White
Green/White
Blue/White
Black/Red
White/Red
Orange/Red
Blue/Red
Red/Green
Orange/Green
Black/White/Red
White/Black/Red
Red/Black/White

#### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.387 in	0.04 in

# **Electrical Characteristics**

#### Conductor DCR

Nominal Conductor DCR 15.6 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor 34 pF/ft

#### Inductance

Nominal Inductance

#### Current

Max. Recommended Current [A]

1.5 Amps per conductor @ 25°C

#### Voltage

UL Voltage Rating
300 V RMS (CMG)
150 V RMS (UL AWM Style 2576)

## **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2576)
Operating Temp Range:	-20°C To +80°C

## **Mechanical Characteristics**

Bulk Cable Weight:	101 lbs/1000ft
Max Recommended Pulling Tension:	228 lbs
Min Bend Radius/Minor Axis:	4 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2576 (150 V 80°C)
CPR Euroclass:	Eca

# **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (CMG)

#### Plenum/Non-Plenum

#### **Part Number**

#### Variants

Item #	Color	Putup Type	Length	UPC
8459 060100	Chrome	Reel	100 ft	612825208075
8459 060500	Chrome	Reel	500 ft	612825208099
8459 0601000	Chrome	Reel	1,000 ft	612825208082
8459 0605000	Chrome	Reel	5,000 ft	612825208105

Footnote: C - CRATE REEL PUT-UP.

#### History

Update and Revision: Revision Number: 0.284 Revision Date: 05-11-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.