



**Product:** <u>8527</u> ⊠

Lead Wire, #12 Str TC, PVC Ins, TYPE MW MIL-W-76C-PVC

# Request Sample

# **Product Description**

Low Temp Plastic Lead Wire, 12AWG (65x30) Tinned Copper, PVC Insulation, TYPE MW MIL-W-76C-PVC 1000V 80C

### **Technical Specifications**

## **Product Overview**

Suitable Applications: inter-connection circuits, internal wiring of computer and electronic equipments, (Type MW) MIL-W-76C-Low Temp applications

## **Physical Characteristics (Overall)**

#### Conductor

| AWG   | Stranding    | Material           | No. of Conductors |
|-------|--------------|--------------------|-------------------|
| 12    | 65x30        | TC - Tinned Copper | 1                 |
| Condu | uctor Count: | 1                  |                   |

#### Insulation

| Material                 | Nominal Diameter | Nominal Wall Thickness |
|--------------------------|------------------|------------------------|
| PVC - Polyvinyl Chloride | 0.128 in         | 0.021 in               |

## **Electrical Characteristics**

## Voltage

UL Voltage Rating 1000 V RMS

# **Temperature Range**

Non-UL Temp Rating: 80°C

## **Mechanical Characteristics**

Bulk Cable Weight: 24 lbs/1000ft

## **Standards**

Military Compliance: MIL-W-76C Type MWP

# **Applicable Environmental and Other Programs**

| EU Directive 2000/53/EC (ELV):     | Yes                           |
|------------------------------------|-------------------------------|
| EU Directive 2003/96/EC (BFR):     | Yes                           |
| EU Directive 2011/65/EU (ROHS II): | Yes                           |
| EU Directive 2012/19/EU (WEEE):    | Yes                           |
| EU Directive 2015/863/EU:          | Yes                           |
| EU Directive Compliance:           | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                        | Yes                           |

| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-10-01 |
|---------------------------------------|------------|
| CA Prop 65:                           | Yes        |
| MII Order #39 (China RoHS):           | Yes        |

## Flammability, LS0H, Toxicity Testing

| UL voltage rating: | N/A |
|--------------------|-----|

### Plenum/Non-Plenum

| Plenum (Y/N): |
|---------------|
|---------------|

### **Part Number**

#### Variants

| Item #       | Color       | Putup Type | Length   | UPC          |
|--------------|-------------|------------|----------|--------------|
| 8527 010100  | Black       | Reel       | 100 ft   | 612825212867 |
| 8527 0101000 | Black       | Reel       | 1,000 ft | 612825212874 |
| 8527 006100  | Blue, Light | Reel       | 100 ft   | 612825212812 |
| 8527 0061000 | Blue, Light | Reel       | 1,000 ft | 612825212829 |
| 8527 0081000 | Gray        | Reel       | 1,000 ft | 612825212836 |
| 8527 005100  | Green, Dark | Reel       | 100 ft   | 612825212799 |
| 8527 0051000 | Green, Dark | Reel       | 1,000 ft | 612825212805 |
| 8527 003100  | Orange      | Reel       | 100 ft   | 612825212768 |
| 8527 0031000 | Orange      | Reel       | 1,000 ft | 612825212775 |
| 8527 002100  | Red         | Reel       | 100 ft   | 612825212744 |
| 8527 0021000 | Red         | Reel       | 1,000 ft | 612825212751 |
| 8527 009100  | White       | Reel       | 100 ft   | 612825212843 |
| 8527 0091000 | White       | Reel       | 1,000 ft | 612825212850 |
| 8527 0041000 | Yellow      | Reel       | 1,000 ft | 612825212782 |

| Footnote: | P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'. |
|-----------|---|
| Footnote: | C - CRATE REEL PUT-UP.  |

# History

| Update and Revision: | Revision Number: 0.282 Revision Date: 08-12-2020 |
|----------------------|--|
|                      |  |

#### © 2020 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.