

**Product: 9221** ☑

# Analog Video, #30 Str TC, 90% TC Braid, PVC Jacket



## **Product Description**

30 AWG stranded (7x38) .012" tinned copper conductor, foam HDPE insulation, tinned copper braid shield (90% coverage), PVC jacket.

# **Technical Specifications**

### **Physical Characteristics (Overall)**

# Conductor AWG Stranding Material Nominal Diameter No. of Coax 30 Stranded TC - Tinned Copper 0.012 in 1 Conductor Count: 1

#### Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.058 in

### Outer Shield Material

Type	Material	Coverage [%]
Braid	Tinned Copper (TC)	90%

#### **Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.097 in

#### **Electrical Characteristics**

#### **Conductor DCR**

Nominal Conductor DCR	Nominal Conductor DCR Conductor Resistance	Nominal Outer Shield DCR	Outer Conductor DCR
100 Ohm/1000ft	100 Ohm/1000ft	11.65 Ohm/1000ft	11.65 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield 17.3 pF/ft

#### Inductance

Nominal Inductance

#### Impedance

Nominal Characteristic Impedance
75 Ohm

### High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.7 dB/100ft
3.6 MHz	1.3 dB/100ft

5 MHz	1.6 dB/100ft
7 MHz	1.9 dB/100ft
9 MHz	2.1 dB/100ft
10 MHz	2.2 dB/100ft
50 MHz	5.1 dB/100ft
70 MHz	6.1 dB/100ft
100 MHz	7.3 dB/100ft
200 MHz	10.5 dB/100ft
400 MHz	15.5 dB/100ft
700 MHz	21.5 dB/100ft
900 MHz	24.8 dB/100ft
1000 MHz	26.6 dB/100ft

### Delay

Nominal Delay

1.3 ns/ft

### Voltage

UL Voltage Rating
30 V RMS

## **Temperature Range**

UL Temp Rating:	60°C
Operating Temp Range:	-40°C To +60°C

## **Mechanical Characteristics**

Bulk Cable Weight:	6 lbs/1000ft
Max. Pull Tension:	14 lbs
Min Bend Radius/Minor Axis:	0.25 in

## **Standards**

UL AWM Style Compliance:	UL Style 1375 (30 V 60°C)
CPR Euroclass:	Eca
RG Type:	Ultra-miniature 59/U Type

## **Applicable Environmental and Other Programs**

Environmental Space:	Indoor/Outdoor
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes

## Flammability, LS0H, Toxicity Testing

IEC Flammability:	IEC 60332-1-2
UL voltage rating:	30 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No		

# **Part Number**

V۶	ıria	an	te

Item #	Color	Putup Type	Length	UPC
9221 010100	Black	Reel	100 ft	612825358848
9221 010500	Black	Reel	500 ft	612825358152
9221 010U500	Black	UnReel	500 ft	612825358862

### **History**

Update and Revision:	Revision Number: 0.238 Revision Date: 08-25-2020

#### © 2020 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.