



Part Number: 9913F7

Low Loss 52 Ohm, RG8, Flexible 10 AWG Stranded BC, Foil + Braid, Belflex® Jacket

Product Description

Low Loss, RG-8/U type, 10 AWG stranded (7x19) .108" bare copper conductor, gas-injected foam HDPE insulation, Duobond® II, tinned copper braid shield (95% coverage), Belflex® jacket.

Technical Specifications

Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)
----------------------	------------------------------

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
10	7x19	BC - Bare Copper	0.108 in	1

Conductor Count:	1
Conductor Size:	10 AWG

Insulation

Material	Nominal Diameter
Gas-injected FHDPE - Foam High Density Polyethylene	0.285 in

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	Bonded Duofoil®	100 %
Braid	2	TC - Tinned Copper		90 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter
PVC - Polyvinyl Chloride	Belflex®	0.405 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
1.1 Ohm/1000ft	1.8 Ohm/1000ft	1.8 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Shield
22.5 pF/ft

Shielding:	Foil + Braid(s)
------------	-----------------

Inductance

Nominal Inductance
0.059 µH/ft

Impedance

Nominal Characteristic Impedance
52 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
10 MHz	0.6 dB/100ft
50 MHz	1.1 dB/100ft
100 MHz	1.5 dB/100ft
200 MHz	2 dB/100ft
400 MHz	3 dB/100ft
700 MHz	4 dB/100ft
900 MHz	4.7 dB/100ft
1000 MHz	5 dB/100ft
2000 MHz	7.5 dB/100ft
2250 MHz	8 dB/100ft
3000 MHz	9.8 dB/100ft
4000 MHz	12.1 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.2 ns/ft	85 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
10 MHz	0.7 dB/100ft
50 MHz	1.3 dB/100ft
100 MHz	1.8 dB/100ft
200 MHz	2.4 dB/100ft
400 MHz	3.4 dB/100ft
700 MHz	4.6 dB/100ft
900 MHz	5.3 dB/100ft
1000 MHz	5.6 dB/100ft
2000 MHz	8.2 dB/100ft
2250 MHz	8.9 dB/100ft
3000 MHz	10.9 dB/100ft
4000 MHz	13.6 dB/100ft

Power Rating

Frequency [MHz]	Max. Power Rating [W]	Nominal Power Rating [W]
5 MHz	3,217 W	3,217 W
10 MHz	2,681 W	2,681 W
50 MHz	1,463 W	1,463 W
100 MHz	1,073 W	1,073 W
200 MHz	805 W	805 W
400 MHz	575 W	575 W
700 MHz	424 W	424 W
1,000 MHz	350 W	366 W
1,500 MHz	278 W	350 W
2,000 MHz	237 W	278 W
3,000 MHz	188 W	252 W
4,000 MHz	157 W	237 W
2,500 MHz		210 W
3,000 MHz		188 W
4,000 MHz		157 W

Voltage

Non-UL Voltage Rating
300 V RMS

VSWR

Frequency [MHz]
5-2250 MHz

Electrical Characteristics Notes:	Actual Impedance specification is 51.5 +/- 2 ohms.
-----------------------------------	--

Temperature Range

Non-UL Temp Rating:	80°C
Operating Temp Range:	-40°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	94 lbs/1000ft
Max Recommended Pulling Tension:	210 lbs
Min Bend Radius/Minor Axis:	3 in

Standards

RG Type:	8/U Type
RG / Series Type:	8/U Type

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
-----------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
9913F7 B59100	Black, Matte	C
9913F7 B591000	Black, Matte	C
9913F7 B59250	Black, Matte	C
9913F7 B59500	Black, Matte	C

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2018 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.