



Product: [83318E](#) 

Electronic, 2 C #24 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

 [Request Sample](#)

Product Description

High Temperature Electronic, 2 Conductor 24AWG (19x36) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Conductors
24	19x36	SPC - Silver Plated Copper	2

Conductor Count:	2
Total Number of Pairs:	1

Insulation

Material	Material Trade Name	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.01 in

Color Chart

Number	Color
1	White
2	Black

Outer Shield Material

Type	Material	Coverage [%]
Braid	SPC - Silver Plated Copper	85 %

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
TFE - Tetrafluoroethylene	Teflon®	0.131 in	0.011 in

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
23 Ohm/1000ft	8 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
26.5 pF/ft	42.4 pF/ft

Inductance

Nominal Inductance
0.12 µH/ft

Current

Max. Recommended Current [A]
4 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
600 V RMS

Temperature Range

Operating Temp Range:	-65°C To +200°C
-----------------------	-----------------

Mechanical Characteristics

Bulk Cable Weight:	14 lbs/1000ft
Max Recommended Pulling Tension:	31.6 lbs
Min Bend Radius/Minor Axis:	1.5 in

Standards

CPR Euroclass:	Eca
Military Specification:	MIL-W-16878/4 (Type E except stranding), (insulated conductors)
Other Specification:	NEMA HP3

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	600 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	UPC	Length	Footnote
83318E 009100	White	612825203940	100 ft	E
83318E 0091000	White		1,000 ft	E
83318E 009500	White	612825203957		E

Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.
-----------	--

Product Notes

Notes:	Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.
--------	---

History

Update and Revision:	Revision Number: 0.297 Revision Date: 12-19-2019
----------------------	--

