



TE CONNECTIVITY (TE) - [Buchanan](#) | [SSB7](#)
SSB7TG050501=TERM BLOCK ASSY

✓ ACTIVE

1546977-5
TE Internal Number: 1546977-5

Get Sample

Compatible Parts & Tooling

[Add to List](#) ▼ ▼ | [Documents](#) | [Features](#) | [Compliance](#) | [Similar Products](#)

PRODUCT DRAWING
English

3D PDF

> [See All Documentation](#)

North America ▼

DISTRIBUTOR	PHONE	STOCK	DATE AS OF	
DIGI-KEY ELECTRONICS	1-800-344-4539	8	2017/10/10	Visit Site

- DOCUMENTATION
- FEATURES
- PRODUCT COMPLIANCE

Product Drawings

[SSB7TGXX0501](#)
PDF
English

CAD Files

[Customer View Model](#)
3D_IGS.ZIP
English

[Customer View Model](#)
3D_STP.ZIP
English

[Customer View Model](#)
2D_DXF.ZIP
English

[3D PDF](#)
PDF
3D

Catalog Pages/Data Sheets

[1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Block Style	Turret (Insulated)
	Product Type	Barrier Strip
Configuration Features	Number of Positions	5
	Number of Rows	1
	Number of Levels	1
Electrical Characteristics	Current Rating (A)	20
	Voltage (V)	600
Body Features	Barrier Style	Dual Barrier
	Tab Plating Material	Brass, Tin
	Color	Black
	Tab Plating Finish	Bright
Contact Features	Terminal Plating Finish	Bright
	Terminal Material	Brass
	Blade Size	.787 x 6.35 mm[.031 x .25 in]
	Terminal Plating Material	Tin
Termination Features	Bottom Termination Style	Quick Connects
Mechanical Attachment	Connector Mounting Type	Panel
	Screw Size	6-32
	Mounting Ears	With
	Mounting Bushing	With
	Mounting Options	End Mounting Ears
	Screw Plating Material	Zinc Chromate
	Mounting Insert	With
	Mounting Angle	Vertical
	Screw Head Type	Phillips



	Screw Material	Steel
	Top Hardware	Binding Combo Head
Housing Features	Centerline (Pitch)	11.1 mm [.438 in]
	Housing Material	Thermoplastic
Dimensions	Wire Range	22 – 12 AWG [.3 – 3 mm²]
	Tab Width	6.35 mm [.25 in]
	Length	80.95 mm [3.187 in]
Usage Conditions	Operating Temperature Range	-60 – 105 °C [-76 – 221 °F]
Industry Standards	UL Flammability Rating	UL 94V-2
Packaging Features	Packaging Method	Package
	Packaging Quantity	90
Other	Comment	Other options available upon request, consult our Product Information Center.
Statement of Compliance	Statement of Compliance PDF	

Compatible Products

> [Contact Product Support](#)

Also in the Series | [SSB7](#)



Barrier Strips (2135)

Customers Also Bought

BOARD-TO-BOARD HEADERS & RECEPTACLES



10 SYSTEM 50 RCPT
ASSY SRST SN
5-104192-2

SURFACE MOUNT RESISTORS



CPF A 0603 300K 0.1%
25PPM 1K RL
CPF-A-0603B300KE1

SURFACE MOUNT RESISTORS



CPF A 0805 10K 0.1%
25PPM 1K RL
CPF-A-0805B10KE1

THROUGH-HOLE RESISTORS



LR1 1% 316R
LR1F316R

About TE Connectivity

For Partners

Customer Support

CALL US

LIVE CHAT

United States

Our Company

Events

TE News Center

Careers

Investors

Corporate Responsibility

Terms and Conditions of
Sale

Distributors

Suppliers



Email or Call Us



Find Authorized Distributors



What's New on TE.com



Product FAQs

Select Country & Language

United States (EN)

Germany (DE)

China (中文)

Japan (日本語)

Afghanistan (EN)

Find Your Country

Terms of Use | Privacy | Cookie Policy | Accessibility | Site Map

© 2017 TE Connectivity Corporation. All Rights Reserved

