

[Connectors](#) > [Terminal Blocks & Strips](#) > [Barrier Strips](#)


✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

> [See All Documentation](#)

TE CONNECTIVITY (TE)

JC6-Q407-08=JC6 ASSEMBLY

[Buchanan](#) | [JC6 Series](#)

2-1546700-6
 TE Internal Number: 2-1546700-6
 Alias ID: JC6-Q407-08

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Barrier Style **Dual Barrier**

Bottom Termination Style **Quick Connects**

Current Rating (A) **5, 20**

Number of Positions **8**

Centerline (Pitch) **9.53mm [.375in]**

> [See All Features](#)

North America ▾

DISTRIBUTOR	QUANTITY	DATE AS OF	
AVNET ELECTRONICS 480-643-2000	30	2017/10/01	>
MASTER ELECTRONICS CORP. 1-888-473-5297	80	2017/09/26	>

GET SAMPLE



SAVE TO LIST ▾



CHECK FOR TOOLING



FIND SIMILAR PRODUCTS



DOCUMENTATION

FEATURES

PRODUCT COMPLIANCE

Product Drawings

[JC6-Q407-XX ASSEMBLY](#)

PDF **(TIFF AVAILABLE)**

English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

Catalog Pages/Data Sheets

BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS

PDF

English

1-1773458-2_BARRIER_STRIPS_QUICK_REFERENCE_GUIDE

PDF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Block Style

Turret (Insulated)

Product Type

Barrier Strip

Configuration Features

Number of Positions

8

Number of Rows

1

Number of Levels

1

Electrical Characteristics

Current Rating (A)

5, 20

Voltage (V)

300, 600

Body Features

Barrier Style

Dual Barrier

Color

Black

Contact Features

Terminal Material

Copper Alloy

Terminal Plating Material

Tin

Termination Features

Bottom Termination Style

Quick Connects

Mechanical Attachment

Connector Mounting Type

Panel

Screw Size

6-32

Mounting Ears

Without

Mounting Options

None

Screw Material

Steel

Screw Plating Material

Zinc Chromate

Top Hardware

Binding Combo Head

Mounting Insert


Without

	Screw Head Type	Combo Phil-Slot
	Mounting Angle	Vertical
Housing Features	Centerline (Pitch)	9.53 mm [.375 in]
	Housing Material	Thermoplastic
Dimensions	Wire Range	22 – 12 AWG [.3 – 3 mm²]
	Length	77.749 mm [3.061 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Package
	Packaging Quantity	90
Other	Comment	Other options available upon request, consult our Product Information Center.
Statement of Compliance	Statement of Compliance PDF	

Compatible Products

[Contact Product Support](#)


Also in the Series | [JC6 Series](#)



[Barrier Strips \(2135\)](#)

Customers Also Bought

FPC CONNECTORS	TERMINAL BLOCK HEADERS & RECEPTACLES	BARRIER STRIPS	RIBBON CABLE CONNECTORS



1MM FFC SMT H ASSY
13P EMBOSS

1-84981-3



8P UNSHROUD 5.0 HDR,
HIGH TEMP

1546931-8



JC6-Q407-12=JC6
ASSEMBLY

3-1546700-0



A/L UNIV HDR 20P RA

5102160-4