



SEARCH



[Printers and Scanners](#) / [Desktop Printers, Labels and Accessories](#) / [Bradyprinter PR Plus Printer, Labels and Accessories](#) / [Bradyprinter PR Plus Printer Labels](#) /

IP Series PermaSleeve Polyolefin Wire Marking Sleeves





IP Series PermaSleeve Polyolefin Wire Marking Sleeves

Part Number:

PS-250-2-WT-2

Material:

Polyolefin

Material Number:

B-342

For Use with Printer:

BRADY IP® Series Label Printer,
BradyPrinter i7100, BRADYPRINTER PR
Plus Series Label Printer

Color:

White

Quantity per Roll:

5000

ADD TO CART

1

PEOPLE ALSO VIEWED

OVERVIEW

PermaSleeve® PS Heat-Shrink Polyolefin (B-342) wire marking sleeves combine speed, ease of use, and permanence to create long-lasting, high quality identification.

- 3:1 heat shrinkable sleeve fit snugly around wires for maximum insulation protection and permanent identification

- Fade-resistant and smudge-proof for superior aesthetic appearance
- Cold resistant and flame-retardant with an operating temperature of -67°F to 275°F (-55°C to 135°C)
- Meets SAE-AMS-DTL-23053/5C (Class 1), SAE-AS-81531, MIL-STD-202; RoHS Compliant; and UL Recognized

SPECIFICATIONS

Material Number	B-342
Diameter as Supplied	0.25 in
Dimensions	0.439 in H
UOM	Roll of 5000 Each
Maximum Service Temperature °F	267 °F
Maximum Wire Diameter	0.215 in
Maximum Wire Gauge	8 AWG
Minimum Service Temperature °F	-94 °F
Minimum Wire Diameter	0.094 in
Minimum Wire Gauge	16 AWG
Printable Sides	Single-Side Printable
Product Number	11217
UPC	662820112174
Quantity per Roll	5000
Quantity per Row	2
Recovered Diameter	0.094 in
Roll Width	2 in
Shrink Ratio	3:1
Sleeve Size	0.25 in Dia x 1 in W
Sleeve Size(m)	6.4 mm Dia x 25.4 mm W
Sleeve Slits	Yes
Sleeve Width	1 in
Trade Name	Brady IP™ PermaSleeve®
Applications	Cable & Wire Marking
Color	White
For Use with Printer	BRADY IP® Series Label Printer, BradyPrinter i7100, BRADYPRINTER PR Plus Series Label Printer
Label/Media Format	Roll

Material	Polyolefin
Material Properties	Heat-Shrinkable, Self-Extinguishing
Print Technology	Thermal Transfer
Resistance Properties	Chemical-Resistant, Corrosion-Resistant, Humidity-Resistant, Smear-Resistant, UV-Resistant, Weather-Resistant
Suggested Ribbon Series	R2000, R4300, R4502S, R5000, R6600, R6700

ACCESSORIES

Solutions

- Floor Marking Guide
- GHS Label Compliance
- Lockout Tagout Compliance
- Arc Flash Labeling Requirements
- Cable and Wire Label Options
- Product and Barcode Labeling
- Brand Protection Solutions

Services

- Lockout Tagout Services
- Arc Flash Services
- Confined Space Services
- Visual Workplace Services
- Hazcom GHS Services
- Software Programming & Integration
- Label Template & File Conversion
- Printer Use & Training
- Printer Preventative Maintenance
- Toll and Custom Coating
- Authentication & Tracking Services

Help

- Contact Us
- Knowledge Center
- Printer Drivers & Firmware
- Brady Software Updates
- Safety Data Sheets
- Technical Data Sheets
- WEEE RoHS Compliance
- Product Certification
- Printer Registration

Resources

- Find a Distributor
- Printer Selection Tool
- Label Selection Tool
- Digital Catalog
- Request a Catalog



Brady (NYSE:BRC) is a manufacturer of complete solutions that identify and protect people, products and places. Brady's products help customers increase safety, security, productivity and

Contact
6555 W. Good Hope Rd. Milwaukee WI 53223
Phone: 888-250-3082
Hours: 7am-6pm CST Monday - Friday

About
Corporation
Privacy Policy
Terms and Conditions
Terms of Use
ISO Certificates

Other
Brady Sites
Distributor Portal
International Sites
Safety Services & Software
Smart ID
Brand Protection



© 2017 Brady Worldwide, Inc.

**performance
and include
high-
performance
labels,
signs, safety
devices,
printing
systems
and
software.**