

[Labels](#) / [Printer Labels and Ribbons](#) / [Portable Printer Labels](#) / [TLS PC Link Thermal Transfer Printer Labels](#) /

BMP61 BMP71 TLS 2200 Self-Laminating Vinyl Wire and Cable Labels



BMP61 BMP71 TLS 2200 Self-Laminating Vinyl Wire and Cable Labels

Part Number:

PTL-23-427-BL

Label/Tape Size:

4 in H x 1 in W

Material:

Vinyl

For Use with Printer:

BMP®61 Labeling System, BMP®71 Label
Printer, TLS 2200® Thermal Labeling
System, TLS-PC LINK™ Thermal Labeling
System

Color:

Blue/Translucent

Material Number:

B-427

ADD TO CART

1

PEOPLE ALSO VIEWED

OVERVIEW

Self-Laminating Vinyl (B-427) is an excellent material for wire and cable identification. This material has good clarity, conformability and is self-extinguishing.

- Provided in a self-laminated format with a white printable zone and translucent overlaminating area to protect text
- Durable, permanent acrylic adhesive has outstanding water and oil resistance
- RoHS compliant to 2005/618/EC MCV amendment to RoHS Directive 2002/95/EC; UL approved
- Service temperature of -40°F to 158°F (-40°C to 70°C)

SPECIFICATIONS

Material Number	B-427
Dimensions	4 in H x 1 in W
UOM	Roll of 100 Labels
Finish	Matte
Indoor or Outdoor Use	Outdoor Use
Label/Tape Size	4 in H x 1 in W
Maximum Service Temperature °F	140 °F
Minimum Service Temperature °F	-40 °F
Overlamine Included	Overlamine Included
Pre-Printed Areas on Label	Colored Write-On Area
Printable Area Dimensions	1 in H x 1 in W
Printable Area Height	1 in
Printable Area Width	1 in
Product Number	18524
UPC	662820185246
Quantity per Roll	100
Quantity per Row	1
Secondary Label Included	Secondary Label is Not Included

Thickness	0.004 in
Trade Name	BMP®61 BMP®71 TLS 2200® TLS-PC Link™
Adhesive Type	Acrylic
Applications	Cable & Wire Marking, Panel Labeling, Voice & Data ID
Color	Blue/Translucent
For Use with Printer	BMP®61 Labeling System, BMP®71 Label Printer, TLS 2200® Thermal Labeling System, TLS-PC LINK™ Thermal Labeling System
Header	No Header
Label/Media Format	Roll
Language	No Text
Material	Vinyl
Material Properties	Flame-retardant, Self-Laminating
Print Technology	Thermal Transfer
Resistance Properties	Chemical-Resistant, Humidity-Resistant, Oil-Resistant, Water-Resistant, Weather-Resistant
Shape	Rectangle
Suggested Ribbon Series	R4300, R6200

Solutions

[Floor Marking Guide](#)
[GHS Label Compliance](#)
[Lockout Tagout Compliance](#)
[Arc Flash Labeling Requirements](#)
[Cable and Wire Label Options](#)
[Product and Barcode Labeling](#)
[Brand Protection Solutions](#)

Services

[Lockout Tagout Services](#)
[Arc Flash Services](#)
[Confined Space Services](#)
[Visual Workplace Services](#)
[Hazcom GHS Services](#)
[Software Programming & Integration](#)
[Label Template & File Conversion](#)
[Printer Use & Training](#)
[Printer Preventative Maintenance](#)
[Toll and Custom Coating](#)
[Authentication & Tracking Services](#)

Help

[Contact Us](#)
[Knowledge Center](#)
[Printer Drivers & Firmware](#)
[Brady Software Updates](#)
[Safety Data Sheets](#)
[Technical Data Sheets](#)
[WEEE-RoHS Compliance](#)
[Product Certification](#)
[Printer Registration](#)

Resources

[Find a Distributor](#)
[Printer Selection Tool](#)
[Label Selection Tool](#)
[Digital Catalog](#)
[Request a Catalog](#)



Brady
(NYSE:BRC)
is a
manufacturer
of complete
solutions
that
identify and
protect
people,
products
and places.
Brady's
products
help
customers
increase
safety,
security,
productivity
and
performance
and include
high-
performance
labels,
signs, safety
devices,
printing
systems
and
software.

Contact
6555
W.
Good
Hope
Rd.
Milwaukee
WI
53223
Phone:
888-
250-
3082
Hours:
7am-
6pm
CST
Monday
-
Thursday;
Friday
7am-
5pm
CST

About
Corporation
Privacy
Policy
Terms
and
Conditions
Terms
of Use
ISO
Certificates

Other
Brady
Sites
Distributor
Portal
International
Sites
Safety
Services
&
Software
Smart
ID
Brand
Protection



© 2018 Brady Worldwide, Inc.