


 All Categories

0 item(s) | \$0.00

[Products](#) | [Markets](#) | [Standards and Compliance](#) | [Customer Support](#) | [Technical Support](#) | [Client Services](#) | [News and Events](#)

[Home](#) > [Printers, Barcode Scanners and Laminators](#) > [Desktop Printers and Accessories](#) > [BBP81 Label Printer and Accessories](#) > [BBP81 Label Printer Labels](#) >



Zoom



Thermal Transfer Printable Labels

Description: Thermal Transfer Printable Labels

Part Number: THT-2-719-10

Product Number: 134304

UPC Code: 75447392486

Height (in): 0.250"

Width (in): 0.900"

Color: White

QTY/UOM: 10,000/Roll

Related Information

- [Request BBP81 Demo](#)
- [Register Your Printer](#)
- [Desktop Printer Comparison Guide](#)

Overview

Specifications

Specifications for Thermal Transfer Printable Labels

Application	Circuit Board ID, Component ID, SMT - Top/Bottom, Through Hole - Bottom, Through Hole - Top, PCB Barcode
Patent Numbers	5958537
Color	White
Brady Material Number	B-719
Agency Approval(s)/Compliance	UL Recognized, ESD-approved for IEC 61340-5-1 and EN 100015-1, EIA-541 "Packaging Material Standards for ESD Sensitive Items"
Web Width	3.350" (85.09 mm)
Vertical Repeat	0.350" (8.89 mm)
Horizontal Repeat	1.125" (28.58 mm)
Material Type	Polyimide
Material Description	High-Temperature ESD Industrial Polyimide Barcode Label
Recommended Ribbon Series	6000, 4700
Suggested Ribbon Part#	R6002, R4702
Acceptable Ribbon Series	4800
Printer Compatibility	Brady 1244, Brady 1344, Brady 2461, Brady 3481, Brady 6441, Brady 300MVP Plus, Brady 200MVP Plus, Brady 300X-Plus II, Brady 360X-Plus II, Brady 600X-Plus II, Tagus T200, Tagus T300, Thermal Transfer Printers, IP300, IP600, BBP81
Through Hole Technology	Top: Yes, Bottom: Yes
Special Properties	ESD rated label that withstands high-temperatures while exhibiting excellent resistance to harsh fluxing and wave solder environments. Resists all commonly employed methods of cleaning
Brand	UltraTemp Series
Height (in)	0.250"
Width (in)	0.900"
Height (mm)	6.350 mm
Width (mm)	22.860 mm
Printable Area (in)	0.900" W x 0.250" H
Printable Area (mm)	22.860 mm W x 6.350 mm H
RoHS Compatibility	Pass 2011/65/EU
QTY/UOM	10,000/Roll

CONTACT US

Contact Us
Find a Distributor
Email Subscription
Brady International Sites
Brady Mobile Site

DISTRIBUTION PARTNERS

Bradyserve.com
Distributor.com
Minimum Advertised Price Policy

CORPORATE INFORMATION

About Brady
Environmental Policy
Bradycorp.com
ISO Certified
Legal

SUPPORT

Email Customer Support
Email Technical Support
Submit Website Feedback
Warranty
Sitemap

