

[All Categories](#) > [Connectors](#) > [Insulation Displacement Connectors- Commercial & MIL SPEC](#) > [Insulation Displacement Connectors- Commercial](#) > [Header Connectors](#) > [Header Connectors](#) > [Fully ShroudedHeader Connectors](#) > [Socket Connectors](#) > [Fully Enclosed Micro Miniature Slide Switches](#) > Item # G-107-0513



larger image

Item # G-107-0513, Fully Enclosed Micro Miniature Slide Switches

Specifications

Circuitry	SPDT
Switch Function	ON-ON
Electrical Ratings ¹	0.5 A @ 125 VACVDC
Terminal	3 Terminal
Actuator Style	Standard
Actuator Height	0.140
Mounting	PC
Orientation	Top
Terminations	PC
Illumination	Non Illuminated
Dielectric Withstand Voltage	2000 volts rms - 1 minute minimum
Capacitance	Less than 1.0 pF
Maximum Operating Temperature (Ambient)	105 °C
Minimum Operating Temperature	-20 °C
Storage Temperature	-40 to 105 °C
Humidity	After 100 hrs. at 95% relative humidity, 50°C and drying for 1 hr. at 27°C, insulation resistance is greater than 10 ⁹ megohms and Soldering - Use no more than 30 watt iron for no more than 4 seconds in contact with terminal
Listing Agency (Consult drawing or factory for specific rating) ²	 Listing Agencies
Compliance	

¹ Recognized under the Component Recognition Program of Underwriter Laboratories. Inc., and certified by Canadian Standards Association. (UL File No. E9556, CSA File No. LR20985)
² Due to ongoing advancements, additional agency certifications may be available, contact us for more information.