

	Mome At	out Us	Products	Investor Relations	News	Contact Us	Secure EAX
Product Navigation							
Circuit Board Indicators							
Panel Mount Indicators	Circuit Board Indicators - Through Hole Indicators  P/N# 5600205F Bi-Pin LED Lamp Single Color						
Solid State Lighting	P/N# <b>5600205F</b>			Lamp single color			
Traffic Signals	Description Package Options		LED Lamp ces Per Bag				
Vehicle Lighting	Product Type	Throu	igh Hole Indicators ete LED				
Rail	Sub Product Type Configuration		LED Lamp				
Obstruction Lighting	Lamp Type Viewing	Single Top V	: Color iew				
Hazardous Area Lighting	Viewing Angle	50					
Heliport Lighting	Absolute Maximu	m Ratir	ngs (Ta=	25°)		Dietvilu	itor Stock Check
have to average							th our distributors
how to purchase sales contacts	Operating Temp		o +100° C			now.	tii our distributors
- stock check	Storage Temp	-55 t	o +100° C			5600205F	
			NoHS /pB Fr			check stock 🔾	2
© search			view F	'DF			
Product Line Search	Operating Char	acterist	tics				
Please select a Product Line to search.  Circuit Board Indicators	LED Position						
find ()	Color		Green				
	Lamp Type		Single Color				
□ Part # / Text Search	LED Type		Resistor				
Part No.:	Intensity Min (mcd)						
Text Search:	Intensity Typ (mcd)		5.8				
	Intensity Max (mcd)						
search()	Fwd Voltage Min						
quick links	Fwd Voltage Typ						
Dialight Corporate Video	Fwd Voltage Max						
Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. <b>Yiew PDF</b> File	Dom Wavelength Min (nm	)	570				
	Dom Wavelength Typ (nm	)					
	Dom Wavelength Max (nn	)					
	Power Dissipation Max (m	W)					
Application Notes FAQs	Backlighting						
	Pitch Between Vertical						
Dialight Ltd (UK) Dialight Garufo Dialight BLP LumiDrives	Pitch Between Horizontal						
	Lum Intensity Min						
	Lum Intensity Typ						
	Lum Intensity Max						

