




Circuit Board Indicators	Circuit Board Indicators - Through Hole Indicators	
Panel Mount Indicators	P/N# 56403401114F	3 mm Lens Single Color
Solid State Lighting		
Traffic Signals	Description	3 mm Tri-Level X4 CBI 5V R-R-R
Vehicle Lighting	Package Options	5 Pieces Per Bag
Rail	Product Type	Through Hole Indicators
Obstruction Lighting	Sub Product Type	with Tri-Level Housing
Hazardous Area Lighting	Configuration	3 mm Lens
Heliport Lighting	Lamp Type	Single Color
	Viewing	Right Angle
	Viewing Angle	60
	Test Current (mA)	5V

how to purchase	Absolute Maximum Ratings (Ta = 25 °)	
sales contacts		
stock check		
search		
Product Line Search		
Please select a Product Line to search.		
Circuit Board Indicators		
find		
Part # / Text Search	Reverse Current	100 @ Vr = 5V
Part No.:	Derating	from 50Â° @ 0.086 V/Â°C
Text Search:	Reverse Voltage	5 V
search	Solder Temp	260Â° for 5 sec
	Operating Temp	-40 to +85° C
	Storage Temp	-55 to +100° C



☐ Part # / Text Search

Part No.:

Text Search:

search

quick links

Dialight Corporate Video

Presentation at LightFair 2007 - "Presentation of White LEDs" : by Ian Ferguson, Georgia Tech in conjunction with Dialight Corp. [View PDF File](#)

Application Notes

FAQs

Dialight Ltd (UK)

Dialight Garufo

Dialight BLP

LumiDrives

Operating Characteristics		
LED Position	1-3	
Color	Red	
Lamp Type	Single Color	
LED Type	Integral Resistor	
Intensity Min (mcd)	8.7	
Intensity Typ (mcd)	29.0	
Intensity Max (mcd)		
Fwd Voltage Min		
Fwd Voltage Typ		
Fwd Voltage Max		
Dom Wavelength Min (nm)		
Dom Wavelength Typ (nm)		
Dom Wavelength Max (nm)		
Power Dissipation Max (mW)		
Backlighting		
Pitch Between Vertical	5.08	
Pitch Between Horizontal		
Lum Intensity Min		
Lum Intensity Typ		
Lum Intensity Max		

Distributor Stock Check

Check stock with our distributors now.

56403401114F

check stock

menu rendered