




ohne Ansaughaube
without hood



Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0.1 mm
Coplanarity Area of Termination ≤ 0.1 mm

Verpackt in Gurtverpackung
Tape on Reel Packaging
Verpackungseinheit: 320 Stück
Packaging unit: 320 pcs



← Abspulrichtung - Reel off Direction



454209		weiß white	0.6	9.0	1.2	8.4	Codierung wie Variante schwarz Encoding such variant black
294652		rot red	4.2	5.4	4.8	4.8	
294651		grün green	3.0	6.6	3.6	6.0	
294650		blau blue	1.8	7.8	2.4	7.2	
294649		schwarz black	0.6	9.0	1.2	8.4	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Information:		Tolerances		Scale	3:1		
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation		M 2.54 SRC-P, 8-polig	
g		30.04.2013		ERNI		www.ERNI.com	
Index		Date				224994	
				Class		SRCP	
						I	
						A2	