

CHARACTERISTICS

Weight: 0,725 Kg / 1,6 Lb

Housing in ZAMAK

Impeller in plastic UL 94 V-0

L-10 life expectancy at 40°C: 80.000 hours

Operating temperature range: -10 / +70 °C

Storage temperature: -54 / +85°C

Connection: Terminals

Impedance Protected



OPTIONS

Speed sensor

Other IP levels

Flying leads connection

Salt spray protection

Shocks and vibrations protection

Marine application

Wide temperature range

Other voltages

Dual voltage 115-230V

Part Number	Voltage	Frequency	Nb Phases	Airflow		Pressure		Nominal speed	Noise level LP	Nominal current	Starting current	power	Capacitor
	V	Hz		l/s	CFM	mm H ₂ O	inch H ₂ O	RPM	dBA	mA	mA	W	μF
125XL0182001	115	50	1	25,0	53,00	2,2	0,09	1600	30	135	145	12	
82	115	60	1	27,0	57,24	2,4	0,09	1750	32	115	125	10	
81	220	50	1	25,0	53,00	2,2	0,09	1600	30	75	90	12	
81	220	60	1	27,0	57,24	2,4	0,09	1750	32	65	75	10	
125LG0182001	115	50	1	35,0	74,20	5	0,20	2200	38	200	260	16	
82	115	60	1	40,0	84,80	5,5	0,22	2500	40,5	160	220	13	
81	220	50	1	35,0	74,20	5	0,20	2200	38	110	140	18	
81	220	60	1	40,0	84,80	5,5	0,22	2500	40,5	90	120	15	
125XR0182001	115	50	1	44,0	93,28	9,5	0,37	2800	44	200	310	16	
82	115	60	1	53,0	112,36	10,5	0,41	3200	48	180	260	15	
81	220	50	1	44,0	93,28	9,5	0,37	2800	44	125	170	18	
81	220	60	1	53,0	112,36	10,5	0,41	3200	48	105	150	15	

