


Datasheet

Item No. 56.203.8653.0

Installation terminal WKIS 2,5NTM-D-SL

Installation terminal block with direct spring connection for mounting on TS 35, nominal cross section 2.5 mm², width 5 mm, color gray



Item No.	56.203.8653.0
EAN	4015573852150
order unit	50 Piece(s)

Approvals



Technical data

General

Nominal cross section	2.5 mm ²
Basic colour	Grey
Number of levels	3
Number of clamp positions per level	2
Width/grid dimension	5 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Mounting method	DIN rail (top hat rail) 35/7.5 mm
Terminal blocks for electrical installations	Yes

Technical data

Rated current	20 A
Rated voltage	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Closing plate required	Yes
Length	100 mm
Type of insulation material	Thermoplastic

Connection Data

Connection type 1	Plug-in connection
Connection type 2	Plug-in connection
Minimum cross section solid	0.14 mm ²
Maximum cross section solid	4 mm ²

Minimum cross section fine stranded	0.14 mm ²
Maximum cross section fine stranded	4 mm ²
Wire strip length	11 mm

Accessories

Remark to rated voltage	400V/250V
Remark to rated current	24A at 4mm ²
N-function	No

Accessories

Item. No.	Typ:	Description:
98.300.0000.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, unslotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.300.1000.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.300.1900.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.360.0000.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.360.0004.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel, hot galvanized
98.370.0000.0	Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.370.1000.0	Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, slotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.380.0000.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material E copper
Z7.280.6227.0	Jumper bar IVBWKF 2,5 - 2	Cross connector, insulated for DIN rail terminal blocks type WKF..., 2 -pole
Z7.280.6327.0	Jumper bar IVBWKF 2,5 - 3	Cross connector, insulated for DIN rail terminal blocks type WKF..., 3 -pole
Z7.280.6427.0	Jumper bar IVBWKF 2,5 - 4	Cross connector, insulated for DIN rail terminal blocks type WKF..., 4 -pole
Z7.280.6527.0	Jumper bar IVBWKF 2,5 - 5	Cross connector, insulated for DIN rail terminal blocks type WKF..., 5 -pole
Z7.280.6627.0	Jumper bar IVBWKF 2,5 - 6	Cross connector, insulated for DIN rail terminal blocks type WKF..., 6 -pole
Z7.280.6727.0	Jumper bar IVBWKF 2,5 - 7	Cross connector, insulated for DIN rail terminal blocks type WKF..., 7 -pole
Z7.280.6827.0	Jumper bar IVBWKF 2,5 - 8	Cross connector, insulated for DIN rail terminal blocks type WKF..., 8 -pole
Z7.280.6927.0	Jumper bar IVBWKF 2,5 - 9	Cross connector, insulated for DIN rail terminal blocks type WKF..., 9 -pole
Z7.280.7027.0	Jumper bar IVBWKF 2,5 - 10	Cross connector, insulated for DIN rail terminal blocks type WKF..., 10 -pole

Legend:

- X = blau eingefärbt (in this section blue printed)
- Y = grün/gelb eingefärbt (in this section green/yellow printed)

Dimensions:

- Top view: 100 (width), 32,5 (width), 50,2 (height), 50,7 (height), 58,2 (height)
- Side view: 5 (width)

Components:

- Hutschiene EN 60715-35x7,5 (mounting rail EN 60715-35x7,5)
- Hutschiene EN 60715-35x15 (mounting rail EN 60715-35x15)

Table:

Freileitung nach		CAD - Zeichnung, keine manuellen Änderungen		1. Verwendung: -		Bl: 1 von 1	
Mo	Stab	Werkstoff und Oberfläche:	2005	Tag	Name	Zeichnung Nr.	
/	2:1	Kieselsäure, abh. RAL 7032	Erstellt	07.07.	Bauer F.	56.203.8653.0 01K	
/		grün, sim. to RAL 7032	Geprüft	-	-	Ersetzt für: -	
/		mm²	mm²				
/		mm²	mm²				
Benennung		Typ		Benennung			
Änderung		WK15 2,5		INSTALLATIONSKLEMME			
		NTM-D-SL		"Steckfeder" 2,5mm			
		Elektrische Verbindungen		installation terminal / spring connection			

Further data see catalog
 further data see catalog