




Datasheet

Item No. 56.704.4055.0

Fuse terminal WKFN 4 TKG / 35

Fuse terminal block with spring clamp connection for mounting on TS 35; nominal cross section 4 mm 2 ; width 6 mm; color gray



Item No.	56.704.4055.0
EAN	4015573935730
order unit	100 Piece(s)

Approvals







Technical data

General

Nominal cross section	4 mm²	
Colour	Grey	
Number of levels	1	
Number of clamp positions per level	2	
Width/grid dimension	6 mm	
Insulating housing	PA666	
Inflammability class of insulation material acc. with UL94	VO	
Mounting method	DIN rail (top hat rail) 35/7.5 mm	
Terminal blocks for electrical installations	No	

Technical data

Rated voltage	500 V	
Rated impulse voltage	8 kV	
Pollution degree	3	
Closing plate required	Yes	
Length	82.2 mm	
Type of insulation material	Thermoplastic	

Connection Data

Connection type 1	Tension clamp connection	
Connection type 2	Tension clamp connection	
Minimum cross section solid	0.13 mm²	
Maximum cross section solid	6 mm²	
Minimum cross section fine stranded	0.13 mm ²	
Maximum cross section fine stranded	4 mm²	
Wire strip length	11 mm	

Accessories

Remark to rated current	Note fuse insert
Integrated test socket	No





Accessories

Accessories		
Item. No.	Тур:	Description:
04.343.6153.8	Warning cover ADF 4/4 YELLOW	Cover with warning symbol for DIN rail terminal blocks type WKF
98.300.0000.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, unslotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.300.1000.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.300.1900.0	Mounting rail 35x27x7,5EN60715 2000MM	Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.360.0000.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.360.0004.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel, hot galvanized
98.370.0000.0	Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.370.1000.0	Mounting rail 35x27x15(EN60715)2000MM	Mounting rail TS 35, slotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated
98.380.0000.0	Mounting rail 35x24x15 EN60715 2000MM	Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material E copper
Z1.298.1053.0	Fuse disconnect lever THSI 5X20	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1153.0	Fuse disconnect lever THSI 5X20LED 24	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1253.0	Fuse disconnect lever THSI 5X20LED 60	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1353.0	Fuse disconnect lever THSI 5X20GL 250	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1653.0	Fuse disconnect lever THSI 6,3X32	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1753.0	Fuse disconnect lever THSI 6,3X32 LED 24	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1853.0	Fuse disconnect lever THSI 6,3X32 LED 60	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.1953.0	Fuse disconnect lever THSI 6,3X32 GL 250	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.298.2053.0	Fuse disconnect lever THSI 6,3X32 GL 500	Fuse disconnect lever for diconnect terminal blocks selos / fasis / taris
Z1.299.4055.0	Fuse holder SIST /V0	Fuse holder for diconnect terminal blocks selos / fasis / taris
Z1.299.4155.0	Fuse holder SIST-LED /V0	Fuse holder for diconnect terminal blocks selos / fasis / taris
Z1.299.4255.0	Fuse holder SIST- GL /V0	Fuse holder for diconnect terminal blocks selos / fasis / taris
Z5.553.2921.0	Test plug ST 2 / 2.3 RED	Test plug 2,3 mm color red
Z7.261.1227.0	Jumper bar IVBWKF 4- 2	Cross connector, insulated for DIN rail terminal blocks type WKF, 2 -pole
Z7.261.1327.0	Jumper bar IVBWKF 4 - 3	Cross connector, insulated for DIN rail terminal blocks type WKF, 3 -pole
Z7.261.1427.0	Jumper bar IVBWKF 4 - 4	Cross connector, insulated for DIN rail terminal blocks type WKF, 4 -pole
Z7.261.1527.0	Jumper bar IVBWKF 4 - 5	Cross connector, insulated for DIN rail terminal blocks type WKF, 5 -pole
Z7.261.1627.0	Jumper bar IVBWKF 4 - 6	Cross connector, insulated for DIN rail terminal blocks type WKF, 6 -pole
Z7.261.1727.0	Jumper bar IVBWKF 4 - 7	Cross connector, insulated for DIN rail terminal blocks type WKF, 7 -pole
Z7.261.1827.0	Jumper bar IVBWKF 4 - 8	Cross connector, insulated for DIN rail terminal blocks type WKF, 8 -pole
Z7.261.1927.0	Jumper bar IVBWKF 4 - 9	Cross connector, insulated for DIN rail terminal blocks type WKF, 9 -pole
Z7.261.2027.0	Jumper bar IVBWKF 4- 10	Cross connector, insulated for DIN rail terminal blocks type WKF, 10 -pole





Drawings

