




Datasheet

Item No. 56.716.0353.0

Feed-through terminal WKF 16/35PV/WKFN

Supply terminal block with spring clamp connection for mounting on TS 35, nominal cross section 16 mm², width 12 mm, color gray



| Item No. | 56.716.0353.0 |
|------------|---------------|
| EAN | 4015573735330 |
| order unit | 20 Piece(s) |

Approvals







ATEX





Technical data

General

| Nominal cross section | 16 mm ² |
|--|-----------------------------------|
| Colour | Grey |
| Number of levels | 1 |
| Number of clamp positions per level | 2 |
| Width/grid dimension | 12 mm |
| Insulating housing | PA666 |
| Inflammability class of insulation material acc. with UL94 | V0 |
| Explosion-tested version "EEx e" | No |
| Mounting method | DIN rail (top hat rail) 35/7.5 mm |
| Terminal blocks for electrical installations | Yes |
| | |

Technical data

| Rated current | 76 A |
|-----------------------------|---------------|
| Rated voltage | 800 V |
| Rated impulse voltage | 8 kV |
| Pollution degree | 3 |
| Closing plate required | No |
| Length | 82 mm |
| Type of insulation material | Thermoplastic |

Connection Data

| Connection type 1 | Tension clamp connection |
|-------------------|--------------------------|
| Connection type 2 | Tension clamp connection |





| Minimum cross section solid | 4 mm² |
|-------------------------------------|--------|
| Maximum cross section solid | 10 mm² |
| Minimum cross section fine stranded | 4 mm² |
| Maximum cross section fine stranded | 16 mm² |
| Minimum cross section stranded | 16 mm² |
| Maximum cross section stranded | 16 mm² |
| Wire strip length | 15 mm |

Technical Data UL/CSA

| Cross section UL | 24-4 AWG |
|------------------------|----------|
| Voltage UL | 600 |
| Current factory wiring | 75 A |
| Current field wiring | 75 A |
| Cross section CSA | 12-4 AWG |
| Voltage CSA | 600 V |
| Current CSA | 78 A |

Accessories

| Тур: | Description: |
|---------------------------------------|--|
| Warning cover ADF16/4 GELB | Cover with warning symbol for DIN rail terminal blocks type WKF |
| Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, unslotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x27x7,5EN60715 2000MM | Mounting rail TS 35, slotted, size 7,5 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel, hot galvanized |
| Mounting rail 35x27x15(EN60715)2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x27x15(EN60715)2000MM | Mounting rail TS 35, slotted, size 15 mm, length 2 m, material steel. galv. zinc-plated and dichromated |
| Mounting rail 35x24x15 EN60715 2000MM | Mounting rail TS 35, unslotted, size 15 mm, length 2 m, material E copper |
| Test plug ST 2 / 2.3 RED | Test plug 2,3 mm color red |
| Jumper bar IVBWKF 4- 2 | Cross connector, insulated for DIN rail terminal blocks type WKF, 2 -pole |
| Jumper bar IVBWKF 4 - 3 | Cross connector, insulated for DIN rail terminal blocks type WKF, 3 -pole |
| Jumper bar IVBWKF 4 - 4 | Cross connector, insulated for DIN rail terminal blocks type WKF, 4 -pole |
| Jumper bar IVBWKF 4 - 5 | Cross connector, insulated for DIN rail terminal blocks type WKF, 5 -pole |
| Jumper bar IVBWKF 4 - 6 | Cross connector, insulated for DIN rail terminal blocks type WKF, 6 -pole |
| Jumper bar IVBWKF 4 - 7 | Cross connector, insulated for DIN rail terminal blocks type WKF, 7 -pole |
| Jumper bar IVBWKF 4 - 8 | Cross connector, insulated for DIN rail terminal blocks type WKF, 8 -pole |
| Jumper bar IVBWKF 4 - 9 | Cross connector, insulated for DIN rail terminal blocks type WKF, 9 -pole |
| Jumper bar IVBWKF 4- 10 | Cross connector, insulated for DIN rail terminal blocks type WKF, 10 -pole |
| Jumper bar IVBWKF 2,5 - 2 | Cross connector, insulated for DIN rail terminal blocks type WKF, 2 -pole |
| Jumper bar IVBWKF 2,5 - 3 | Cross connector, insulated for DIN rail terminal blocks type WKF, 3 -pole |
| | Warning cover ADF16/4 GELB Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x27x7,5EN60715 2000MM Mounting rail 35x24x15 EN60715 2000MM Mounting rail 35x24x15 EN60715 2000MM Mounting rail 35x27x15(EN60715)2000MM Mounting rail 35x27x15(EN60715)2000MM Mounting rail 35x27x15(EN60715)2000MM Test plug ST 2 / 2.3 RED Jumper bar IVBWKF 4 - 2 Jumper bar IVBWKF 4 - 3 Jumper bar IVBWKF 4 - 6 Jumper bar IVBWKF 4 - 6 Jumper bar IVBWKF 4 - 7 Jumper bar IVBWKF 4 - 8 Jumper bar IVBWKF 4 - 9 Jumper bar IVBWKF 4 - 10 Jumper bar IVBWKF 4 - 10 Jumper bar IVBWKF 2,5 - 2 |





| Z7.280.6427.0 | Jumper bar IVBWKF 2,5 - 4 | Cross connector, insulated for DIN rail terminal blocks type WKF, 4 -pole |
|---------------|----------------------------|--|
| Z7.280.6527.0 | Jumper bar IVBWKF 2,5 - 5 | Cross connector, insulated for DIN rail terminal blocks type WKF, 5 -pole |
| Z7.280.6627.0 | Jumper bar IVBWKF 2,5 - 6 | Cross connector, insulated for DIN rail terminal blocks type WKF, 6 -pole |
| Z7.280.6727.0 | Jumper bar IVBWKF 2,5 - 7 | Cross connector, insulated for DIN rail terminal blocks type WKF, 7 -pole |
| Z7.280.6827.0 | Jumper bar IVBWKF 2,5 - 8 | Cross connector, insulated for DIN rail terminal blocks type WKF, 8 -pole |
| Z7.280.6927.0 | Jumper bar IVBWKF 2,5 - 9 | Cross connector, insulated for DIN rail terminal blocks type WKF, 9 -pole |
| Z7.280.7027.0 | Jumper bar IVBWKF 2,5 - 10 | Cross connector, insulated for DIN rail terminal blocks type WKF, 10 -pole |

Drawings

