

Datasheet

Art.No. 99.800.4866.1

Flat cable outlet FCS 4 7 SI BU SW FM

Flat cable outlet, pluggable FCS 4 7 SI BU FM; with fix mounting plate for Obo-Bettermann wire tray; 7-pole, 20 A; 277/480 V 4 kV/3(VDE); 600 V (UL, CSA); socket with plastic locking lever; Protection type IP65 plugged or with protective cover 07.409.7256.0; black



Art.No.	99.800.4866.1
EAN	4049088077388
Order unit	5 pieces

Approvals

Technical data

General

Colour	Black
Degree of protection (IP)	IP65
Rated cross section power bus	4 mm ²
Operating temperature min.	-30 °C
Operating temperature max.	55 °C
Storage temperature / transport min.	-40 °C
Storage temperature / transport max.	70 °C

Technical data

Rated voltage	500 V
Rated current	20 A
Rated operating voltage auxiliary power	50 V
Rated operating current auxiliary power	20 A
Number of poles	7
Number of clamp positions per pole	1
Connection type 1	Insulation piercing connection
Connection type 2	Plug-in connection
Cold storage EN 60068-2-1	96h, -30°C
Humid storage EN 60068-2-78	96h, 55°C, 95% r.H.
Mounting method	wire tray

Dimensions

Length	140 mm
Assembly width	60 mm
Assembly height	62 mm