

Datasheet

Item No. Z1.298.1853.0

Fuse disconnect lever THSI 6,3X32 LED 60

Fuse disconnect lever for disconnect terminal blocks selos / fasis / taris



Item No.	Z1.298.1853.0
EAN	4015573712263
order unit	10 Piece(s)

Approvals



Technical data

General

Colour	Grey
Width/grid dimension	8 mm
Insulating housing	PA666
Inflammability class of insulation material acc. with UL94	V0
Mounting method	Direct mounting
Fuse insert	G-fuse 6.3x32 mm

Technical data

Rated voltage	500 V
Closing plate required	No
Length	57.3 mm
Type of insulation material	Thermoplastic

Accessories

Remark to rated voltage	Note fuse insert
Remark to rated current	Note fuse insert
Defect indicator	LED
Minimum operating voltage of defective display	24 V
Maximum operating voltage of defective display	60 V

Baubreite/width 8 mm

Vorderansicht/front view M 1:1

Rückansicht/rear view M 1:1

**Weitere Daten siehe Katalog
further data see catalog**

**Do not disconnect under load.
Ne debrancher pas sous charge.**

Zulässige Abweichungen nach DIN 7167/Permissible deviations acc. to DIN 7167.
(This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).

Freitoleranz nach General tolerance -

CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed

1. Verwendung: First Use:

Blatt: 1 von Sheet: 1 of 1

Zeichnung Nr./Drawing No.

Index

Maße in mm/Dimensions are in mm

wieland Elektrische Verbindungen

Type

Benennung/Title FUSE DISCONNECT LEVER LED SI_TRENNHEBEL_LED

f.Feinsicherung 6,3x32 max. 10A/ LED 24-60 V for fuse 6,3x32 max. 10A/ LED 24-60 V

THS16, 3x32 LED 24

Ersatz für/Replacement for: -

1 2 3 QU-PEM-08/91