
AS85049/82, AS85049/83 and AS85049/84 Straight, 45° and 90° Banding Backshells with Self-Locking Coupling



CONNECTOR DESIGNATOR:

AS50151 Series AS34001 MIL-DTL-26482 Series II AS81703 Series III MIL-DTL-83723 Series I and III 40M39569, DEF 5326-3, EN 2997, EN 3646 ESC 10, ESC 11, LN 29504 NFC93422 Series HE302 PAN 6432-1, PAN 6432-2, PATT 602



Finish

N = Electroless Nickel

P = Cadmium, Olive Drab over Electroless Nickel with Polysulfide Sealant Strips


W = 1,000 Hr. Cadmium Olive Drab over Electroless Nickel

X = Aluminum, Nickel Fluorocarbon Polymer

YP = Aluminum, Pure Dense Electrodeposited Aluminum with Polysulfide Sealant Strips

Z = Aluminum, Zinc-Nickel, Black

ZP = Aluminum, Zinc Nickel with Polysulphide Sealant Strips



APPLICATION NOTES

- Assembly identified with manufacturer's name and part number, space permitting.
- 2. For complete dimensions, see the applicable Military Specification.
- 3. Metric dimensions (mm) are in parentheses.
- 4. For use with AS85049/128 Bands.

Dimensions in inches (millimeters) and are subject to change without notice.

© 2013 Glenair, Inc. U.S. CAGE Code 06324 Printed in U.S.A.