

[Custom Capabilities](#)[Test Accessories](#)[Plugs, Jacks, Posts](#)[Connectors](#)[Hardware](#)[Site](#)[Home](#)[About Abbatron](#)[Products](#)[Locate Distributor
or Representative](#)[Contact Us](#)[Request Information](#)[Site Map](#)

Inventory Search

Cross Reference

UPS Tracking

632 Arch Street, POB 726
Meadville, PA 16335 USA
814-724-6440
Contact Webmaster
© 2006

Dual Instrument Test Adapters



1682

- Insulated dual binding posts to standard dual banana plugs.
- ABS body contains banana jack holes for standard banana plugs. Banana plug springs are Beryllium Copper.
- Available in black body; one red, one black head. 3/4" standard centers.



1697

- BNC female coaxial connector to isolated dual banana plugs.
- Turret terminal connections to isolated from conductors in both ground and hot circuits allow for matching pads or other 4-terminal networks in place of the standard banana plug.
- Available in black ABS body, 3/4" standard centers.



1686

- BNC coaxial jack to dual banana plugs.
- ABS body contains banana jack holes for standard banana plugs. Banana plug springs are Beryllium Copper.
- Available in black body; one red, one black head. 3/4" standard centers.



1687

- BNC coaxial plug to standard dual banana jacks
- ABS body contains banana jack holes for standard banana jacks. Available in black body; one red, one black body. 3/4" standard centers



1688

- Insulated dual binding posts to male BNC connector. MIL UG - 144/U style
- ABS body contains banana jack holes for standard banana jacks. Available in black body; one red, one black body. 3/4" standard centers
- Rated at 15AMPS AC, for 10°C temperature continuous duty, except where limited by coaxial connectors.
- 5KV, 60 cycle AC continuous working voltage where limited by coaxial connectors
- Capacitance:1.0 pf between conductors
- Resistance: 1Milliohm or less per conductor

1698

- Insulated dual binding posts to isolated male plug
- Turret terminal connections to isolated from conductors in both ground and hot circuits all terminal networks in input circuits
- Available in black body; one red, one black body. 3/4" standard centers
- Rated at 15 AMPS AC for 10°C temperature



continuous duty, except where limited by coa

- Capacitance: 1.0 pf between conductors
- Resistance: 1Milliohm or less per conducto



1689

- Insulated dual binding posts to BNC coaxia
- ABS body contains banana jack holes for s
- Available in black body; one red, one black b
- head. 3/4" standard centers
- Rated at 15 AMPS AC for 10°C temperatur
- continuous duty, except where limited by coa
- 5KV, 60 cycle AC continuous working vol
- where limited by coaxial connectors
- Capacitance:1.0 pf between conductors
- Resistance: 1Milliohm or less per conducto

[home](#) | [about abbatron](#) | [products](#) | [locate distributor or representative](#) | [contact us](#) | [request information](#) | [site map](#)