



*Quality Products. Service Excellence.*

## 15 Amp Horizontal Rackmount Surge Strip 1583-S Series

### Rear Mounted Receptacles



### Features

- Designed for power distribution from the rear of the unit.
- 1U horizontal 19" rackmount installation.
- With lighted on/off switch or red pilot light to indicate power on.
- 6 outlet models include 2 outlets with extra spacing for clearance of most plug in transformers.
- Available in ASA 61 grey or black powder coat finish.
- [Click here for our non-surge protected version.](#)

### Specification

- Heavy duty 14 gauge wire cord - 14/3 SJT type for extreme temperature ranges and integral molded plug.
- Plug types available are NEMA 5-15P straight blade or NEMA L5-15P locking type.
- Includes 15 Amp, 125 VAC circuit breaker to prevent accidental overload.
- Surge protected panels incorporate our surge module:
  - Max Energy (Joules) is 1080 J.
  - 25000 Amp rated MOV's for a total of 75,000 Amps of single pulse transient current.
  - Voltage Protection Rating (Vpr) of 500V, in all 3 modes (L-N, L-G, N-G).
  - Nominal Discharge Current (In) of 5kA.
  - Voltage suppression at the outlet guards against transients from equipment on the outlet strip.
- cRUus recognized to UL 1449 & C22.2 No. 269.3-17 & No. 269.4-17, for Surge Protective Devices – Type 3 & Type 4.
- cRUus recognized to UL 1363 & C22.2 No. 308-18, for Relocatable Power Taps & Multi Outlet Assemblies.



### Accessories

- Mounting Hardware
- Rail Depth Adapter Kit

| Black<br>Part No. | ANSI 61 Gray<br>Part No. | Overall Dimensions |       |       | Number of Outlets |      | Outlet<br>NEMA<br>Type | Cord<br>Length | Plug<br>Blade<br>Type | NEMA<br>Plug<br>Type | Rack<br>Units |
|-------------------|--------------------------|--------------------|-------|-------|-------------------|------|------------------------|----------------|-----------------------|----------------------|---------------|
|                   |                          | Height             | Width | Depth | Front             | Rear |                        |                |                       |                      |               |
| 1583H6A1SBK       | 1583H6A1S                | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R                  | 6 ft           | Straight              | 5-15P                | 1U            |
| 1583H6B1SBK       | 1583H6B1S                | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R                  | 15 ft          | Straight              | 5-15P                | 1U            |
| 1583H6C1SBK       | 1583H6C1S                | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R                  | 6 ft           | Locking               | L5-15P               | 1U            |
| 1583H6D1SBK       | 1583H6D1S                | 1.72               | 19.00 | 2.66  | 0                 | 6    | 5-15R                  | 15 ft          | Locking               | L5-15P               | 1U            |
| 1583H8A1SBK       | 1583H8A1S                | 1.72               | 19.00 | 2.66  | 0                 | 8    | 5-15R                  | 6 ft           | Straight              | 5-15P                | 1U            |
| 1583H8B1SBK       | -                        | 1.72               | 19.00 | 2.66  | 0                 | 8    | 5-15R                  | 15 ft          | Straight              | 5-15P                | 1U            |

*Data subject to change without notice*

