

HBL45985CL -- VARILOAD Twist-Lock Flanged Inlet

4P5W, 20A 3PH 120/208V AC Max, Non-NEMA, White Nylon

Product Specifications

Product Type	 Variload Devices
Product Item	Flanged Inlet
Wiring Scheme	4-Pole, 5-Wire Grounding
Amperage	20A
Voltage	3 Phase Y 120/208V AC- 400 Hz
Center Pin Variety	images/905pin.jpg
Device Color	Black
Blade Material	Brass
Terminal Clamp Material	Cold rolled steel-nickel-plated
Terminal Screw Material	#10-32 Brass
Ground Screw Material	Steel (green finish)
Flanged Casing Material	Natural White Nylon
Mounting Screw Material	Nickel-plated Brass Round head screws
Ratings	Molded In or Stamped On
Catalog No	Permanently ink marked on product
Dielectric Voltage Withstand	2,000V minimum
Current Interrupting	Certified for current interrupting at full rated current
Temperature Rise	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
Terminal Accommodation	20A #12 AWG
Terminal Identification	Terminals identified in accordance with UL 498 (X, Y, Z, White, Green)
Flammability	UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors.
Operating Temperatures	Maximum Continuous 75 C Minimum -40 C (w/o impact)
Listings	UL
UPC Number	783585238203
Weight in LBs	0.45
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

CENTER PIN

CONFIGURATION

Center Pin Configuration

