

NHC1035ZP -- Cord Connectors



Machined
Zinc-Plated SteelA

The zinc-plated steel cord connectors offers the strength of steel and the corrosion resistance of zinc-plating. These heavy-duty connectors hold up to most manufacturing chemicals including acid solutions, solvents and other corrosive materials.

Product Specifications	
Product Type	Cord Connectors
Material/Style	Zinc Plated Steel
Cord Diameter Range	.38"- .50" (9.7- 12.7)
Cord Connector Body Style	90 Degree Male
Form Size	F3
HUB Size	3/4"
Color Code	Blue
Effective Operating Temperature	-30°F to +225°F (-34°C to +107°C)
Recommended Knockout Hole Size	1.09"- 1.14" (27.8-29.0)
Flammability	Hubbell nylon cord connectors have a UL 94- V2 rating.
Hazardous Locations	Hubbell cord connectors are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 N.E.C. Reference 501-4(b), 502-4(a), 502-4(b), 503-3(a), and 503-3(b).
Dimension A	1.88" (47.8)
Dimension B	2.90" (73.7)
Dimension C	.56" (14.2) Ref.
Dimension D	.77" (19.4) Throat. Dia.
Dimension E A/C	1.52" (38.6)
Dimension E A/F	1.33" (33.8)
Dimension G A/C	1.55" (39.2)
Dimension G A/F	1.38" (34.9)
Certifications	UL Listed in accordance with Standard 514B, CSA Certified, United States Coast Guard Approval, Title 46-Part 111.
UPC Number	78358521135
Weight in LBs	0.55
Link to Drawing Library	Click here for Library
Link to PDF Catalog	Click here for Catalog

