
Email







☑ Share

Print

Pricing & Availability

Request Sample

Distributor

Add to My Part List

Buy Product through

Support Center

Innovation

Products Industries About TE My Account Resources

Home > Products > Product Feature Selector > Product Details

DT06-12SD-B016 Product Details



Active

Niew 3D PDF



DT Environmentally-Sealed Connectors

DT PLUG ASM

DT06-12SD-B016 /

TE Internal Number: DT06-12SD-B016

Product Highlights View All

- DT Series
- Wire-to-Wire
- Applies To Plug
- Connector
- Plug

Documents Feature	Compliance			Related Products
Please Note: Use the Product Drawing fo	Not quite the product you're looking for? Find Similar Products			
Product Type Features		Housing Features	Housing Features	
Product Type	Connector	Connector Style	Plug/Receptacle	View Part in Product Feature Selector
Connector Type	Plug	Housing Material	Thermoplastic	Check for Tooling

Mating Alignment Type Keyed

Housing Color

Mating Alignment

Froduct Type	Connector
Connector Type	Plug
Wire Insulation Diameter (mm [in])	2.24 - 3.68 [0.088 - 0.145]
Wire/Cable Type	SXL, GXL & TXL
Sealed	Yes
Mechanical Attachment	
Contact Retention	With
Contact Retention Type	Retention Finger/Locking Wedge
Mating Retention Type	Latch(ing)
Electrical Characteristic	CS
Electrical Characteristic Contact - Rated Current (A)	13
Contact - Rated	
Contact - Rated Current (A) Operating Voltage	13
Contact - Rated Current (A) Operating Voltage Reference Operating Voltage	13 DC
Contact - Rated Current (A) Operating Voltage Reference Operating Voltage	13 DC
Contact - Rated Current (A) Operating Voltage Reference Operating Voltage (VDC)	13 DC
Contact - Rated Current (A) Operating Voltage Reference Operating Voltage (VDC) Termination Features	13 DC 250

Seal Type	Grommet
Dimensions	
Contact Qty Size 16	12
Body Features	
Wire Type	Stranded
Cable Exit Angle	180°
Mating Retention	With
Contact Features	
Contact Type	Socket
Contact Layout	In-Line

Configuration Features	
Number of Positions	12
Industry Standards	
RoHS/ELV Compliance	RoHS compliant, ELV compliant
RoHS/ELV Compliance History	Always was RoHS compliant
UL Flammability Rating	UL 94V-0
Identification Marking	
Keying	With
Environmental	
Operating Temperature (°C [°F])	-55 - +125 [-67 - +257]
Conditions for Usage	
Applies To	Plug
Operation/Application	
Application Use	Wire-to-Wire
Contact Transmits (Typical Application)	Signal/Power
Other	

Brown

With

Corporate Information

About TE Investors News Room Supplier Portal Careers

Terms & Conditions Privacy Policy Global Accessibility Statement Quick Links

Distributor Inventory Product Cross Reference Documents & Drawings Product Compliance Support Center Site Map

Series

Brand

Customer Support Email or Chat With Us

DT

DEUTSCH

Find a Phone Number Knowledge Base Manage Your Account Keep Me Informed







