Product Families

- Automation
- Hazardous Location
- Industrial Components
- LED Lighting & Signaling
- Machine Safety
- Sensing

HS6E-M44B05-G
Safety Switch Spring Lock

Add to Cart

Key Features

- 15-mm-wide, thinnest solenoid type interlock switch in the world
- Flexible installation- reversible mounting and angled cable allow four actuator insertion directions
- Energy saving- 24V DC/110 mA
- Manual unlocking possible on three sides
- LED indicator shows solenoid operation
- Standard 3m cable (1m and 5m cable available on request)
- Only proprietary actuators can be used, preventing unauthorized access (ISO14119, EN1088)
- 500N min actuator locking strength (GS-ET-19)
- NC contacts are direct opening (IEC/EN60947-5-1)
- IP67 (IEC60529)
- B10d: 2.0E+06

Specifications | Literature | Related

Product Type	Locking Solenoid Safety Switch
Lock Method (actuator inserted)	Spring Lock
Unlock Method	Energize Solenoid
Solenoid Voltage	24V DC
Indicator Light	Green
Main Contacts	1NC+1NC
Actuator Monitor Contacts	2NC
Solenoid Monitor Contacts	1NC
Cable Length	5m
Retention Force	500N

© 2018 IDEC Corporation All rights reserved. Use of, and copying from, this site is subject to our terms conditions.