

■ **ULTRATORCH® MODEL UT-50**



Quick Jump:

Ultratorch Model UT -50

▼

A professional quality, butapowered soldering iron, flameless heat tool and butane torch


- Standard with protective cap, soldering and heat tip
- Pen -sized heat tool fits in your shirt pocket for absolute portability. No outlets required.
- Aluminum fuel tank with viewing window to indicate fuel level
- Optional tips and accessories available
- Operates for approximately 20 minutes at #3 setting
- UL & GS/TUV Listed for user safety
- Use to pinpoint heat, remove surface mount components, repair vinyl, shrink heat shrink tubing, solder and desolder, spot dry, torch materials and more



ORDERING INFORMATION

MODEL NO.	DESCRIPTION
UT-50	Cordless, butane gas, soldering/heat tool

OPTIONAL ACCESSORIES



PART NO.	DESCRIPTION
71 -01 -01	1 mm dia. tapered needle
71 -01 -02	2.4 mm dia. chisel (std.)
71 -01 -03	2 mm dia. spade tip
71 -01 -04	3 mm dia. spade tip
71 -01 -50	2.3/1.5 heat tip
71 -01 -52	5.6/4.7 heat tip (standard)
70 -01 -55	Heat shrink attachment
70 -01 -54	Heat shrink attachment

SPECIFICATIONS

■ Dimensions: 6.5" L (165 mm)	■ Equivalent to Electric Iron: 20 to 60 Watt
■ Recommended Fuel: Master Ultratane® Butane	■ Gas Tank Capacity: .2 fl. oz. (6 cc)
■ Approx. Operating Time: 20 min.	■ Net Weight: 2.2 oz. (53 g)
■ Approx. Heat Tip Temp.: 806° F (430° C)	■ Shipping Weight: 1 lb.
■ Approx. Solder Tip Temp.: 392° F to 842° F (200° C to 450° C)	■ Shipped Empty
■ Approx. Torch Tip Temp.: 2372° F (1300° C)	

[View Replacement Parts List](#)



ULTRATANE® BUTANE

Use Master Ultratane Butane for best performance. The only approved butane recommended to fuel all Master butane powered products.

Users should independently evaluate the suitability of the product for their application.

WARNING

The Department of Transportation Hazardous Material Regulations forbid carriage of butane or other flammable gas products on passenger aircraft. Do not pack this item or any other flammable gas item in any checked or carry-on baggage.