


PART#/PRODUCT SEARCH

55-71300W-0

GO >>[Item Index](#)[Mode Catalog](#)[Lenline Part# Convert](#)[AC Adapters](#)[Audio Products](#)[Battery Holders](#)[Bottles and Dispensers](#)[Brushes](#)[Buzzers/Alarms](#)[CATV Products](#)[Circuit Breakers](#)[Coaxial Connectors](#)[Computer Accessories](#)[Connectors](#)[DC Power Products](#)[Earphones/Microphones](#)[Fans](#)[Fuseholders/Fuses](#)[Hardware](#)[IC Sockets](#)[Knobs](#)[LED Products](#)[Lamps/Pilot Lamps](#)[Miscellaneous Items](#)[Plastic Boxes](#)[Potentiometers/L-Pads](#)[Power Cords/Jacks/Bars](#)[RF Adapters](#)[Relays](#)[Rubber Feet/Grommets](#)[Speakers/Speaker Wire](#)[Switches](#)[Telephone Products](#)[Test Equipment](#)[Tools/Tool Cases](#)[Transformers](#)[Video Products](#)[Wiring Products](#)[Latent Fingerprint Brush](#)[Enlarge](#)[How to wire LED Strips](#)
[LED Strip Specifications](#)**OUTDOOR LED STRIP 5m WHITE**

- Input Voltage: DC 12V Regulated
- Forward Current: 0.4A per 1m (60 pcs LED Strip)
- Power Dissipation: 4.8W per 1m (60 pcs LED Strip)
- Waterproof IP65: 6 - Totally protected against dust, 5 - Protected against low pressure jets of water from all directions - limited ingress permitted
- Operating Temperature: -20°C ~ 50°C

Len.[m] / LED[PCS] 5 / 300**Material Type** InGaN**Emitted Color** White**Lumen / meter** 390**Dom. Wavelength [nm]** n/a**Color Temp. [CCT]** 6000**View Angle** 120**55-71300W-0** [Bulk](#)

Very bright & low power consumption. Long life span LED lights, more than 50,000 hours. Adhesive back, peel & stick.