

Solutions for Electronic Specialty Markets (ESM)


Product Catalog for Electronic Specialty Markets

- 3M Electronic Specialty Markets New Product Releases
- 3M Abrasives
- 3M Adhesives, Cleaners & Compounds
- 3M Breadboards & Test Clips
- 3M Cable & Assemblies
- 3M Copper Interconnects
- 3M Fiber Optics
- 3M Fire Protection
- 3M Heat Shrink
- 3M Identification Systems
- 3M Occupational Health & Safety Products
- 3M Protective Bumpers
- 3M Reclosable Fasteners
- 3M Splicing, Terminating & Ducting
- 3M Static Control
- 3M Tapes
- 3M Terminals, Kits & Tools
- 3M Vacuums & Accessories
- 3M Warehousing & Packaging Supplies
- 3M Wire Connectors

[Product Catalog for Electronic Specialty Markets](#) [3M Terminals, Kits & Tools](#) [Disconnects](#) [Scotchlok Female Disconnects](#) - [Nylon Insulated w/ Insulation Grip](#)

3M Scotchlok Nylon Insulated w/Insulation Grip Female Disconnect MNG18 -250DFK, 22-18 AWG

 [Printer-friendly format](#)



This terminal has a wire range of 22 - 18 AWG and has case quantities of 1000 per case.

[\[click to enlarge\]](#)

GTIN(UPC/EAN) : 0 00 54007 02369 2
3M Id : 80 - 6100 - 6470 - 3


Additional Information

The disconnects are attached to mating part by tongue of female part slipping over male tab. The use of dents and rolled edges on female part provides excellent holding force while allowing easy and quick disconnect.

Learn More . . .

- [Packaging Data](#)
- [Female Disconnects - Nylon Insulated with Insulation Grip - Product Selection Guide \(PDF 23.1 K\)](#)
- [Scotchlok Terminals MNG18 -250DF, MNG14 -250DF - Data Sheet \(PDF 30.0 K\)](#)
- [Terminal Stud Size Chart - Product Selection Guide \(PDF 5.2 K\)](#)

Please Note:
Adobe® Acrobat® Reader is required to view PDF documents.



Other Tools

- What's New
- Sales Contacts
- U.S. Distributors

Search This Product Catalog

By Keyword

Go

Characteristics

Agency Approvals	UL and CSA
Barrel Style	Insulation Grip
China RoHS - Below MCV	Yes
CSA File Number	LR22190
EPC Can View	Public
EU RoHS Compliant	Yes
Fastener Orientation	Female
Insulation Material	Nylon
Pad Width	0.250 Inch
Terminal Style	Standard
Terminal Type	Disconnect
UL File Number	E70512
Wire Gauge Range	18 to 22 American Wire Gauge (AWG)