

Search This Product Catalog

By Keyword

Go

Marine Products


Product Catalog for Marine

- 3M Abrasive Accessories
- 3M Abrasives
- 3M Adhesives, Sealants and Fasteners
- 3M Cleaning Products
- 3M Compounds, Glazes and Buffing Pads
- 3M Conspicuity Tapes
- 3M Electrical Products
- 3M Fiberglass Fillers
- 3M Lubricants
- 3M Masking Films, Sheeting, Papers, and Tapes
- 3M Matting Products
- 3M Paint & Varnish Remover & Accessories Products
- 3M PPS Paint Preparation System
- 3M Reflective Products
- 3M Safety Products
- 3M Tape and Scotch Tapes
- 3M Wax and Maintenance Products
- 2006 Marine Products & Systems Catalog
- Auto Body Repair Products (Bondo , Dynatron , Marson , and Mar - Hyde)
- Scotchgard Paint Protection Film & Scotchcal Striping Tape
- Thinsulate Acoustic Insulation

[Product Catalog for Marine](#) [3M Electrical Products](#) [3M Electrical Terminals](#) [3M Scotchlok Fully Nylon Insulated Butted Seam Female Disconnect](#)

3M Scotchlok Fully Nylon Insulated Butted Seam Female Disconnect MNU18 -250DFIX, 22 -18 AWG

[Printer-friendly format](#)



This terminal has a wire range of 22 - 18 AWG and has case quantities of 500 per case.

[\[click to enlarge\]](#)

GTIN(UPC/EAN) : 0 00 54007 02286 2
3M Id : 80 - 6100 - 5763 - 2
Buyer's Part Number : 02286

Additional Information

The disconnects are attached to mating part by tongue of female part slipping over male tab. The use of dents and rolled edges on female part provides excellent holding force while allowing easy and quick disconnect.

Learn More . . .

[Packaging Data](#)

- Email [Female Disconnects - Nylon Fully Insulated Butted Seam - Product Selection Guide \(PDF 19.0 K\)](#)
- Email [Scotchlok Terminals MNU18 - 250DFI/MNU14 - 250DFI - Data Sheet \(PDF 37.0 K\)](#)
- Email [Terminal Stud Size Chart - Product Selection Guide \(PDF 5.2 K\)](#)

Please Note:
Adobe® Acrobat® Reader is required to view PDF documents.



Characteristics

Agency Approvals	UL and CSA
Barrel Style	Butted
China RoHS - Below MCV	Yes
CSA File Number	LR22190
EPC Can View	Public
EU RoHS Compliant	Yes
Fastener Orientation	Female
Insulation Material	Nylon
Pad Width	0.250 Inch
Terminal Style	Fully Insulated
Terminal Type	Disconnect
UL File Number	E70512
Wire Gauge Range	18 to 22 American Wire Gauge (AWG)