

Ø15.00

[.59]

Ø5.4 [.21]

Ø10.50


[.41]

80.40 [3.16]

97.0

[3.82]

- RED LED



## SPECIFICATION:

Ø8.64 [.34]

Ø20.00

[.79]

BODY: PBT (VO) + GF, UL FILE #E130155

COLOR: BLACK

CENTER CONTACT: BRASS, NICKEL PLATED

NEG. TERMINAL: SK5, GOLD PLATED POS. TERMINAL: P.B., GOLD PLATED SPRING: ØO.8 P.B. WIRE, GOLD PLATED

WIRE STRAIN RELIEF: PVC

LED: RED, Ø3mm, 2.2K Ohm, 1/4 W

FUSE: 20AMP., 6.35mm x 30mm (1/4" X 1 1/4")

RATED AT 18 HOURS, CONTINUOUS DUTY

20 AMP'S MAX ROHS COMPLIANT

Tolerance (Inches)	Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735				
Decimal			Scale	Drawn By	B.S.
±.5 (.020)				Approved	ву Т.В.
Fractional ± .8 (.030)	Title 20 AMP CIGARETTE PLUG FOR 21 OR 22.2mm DIA. SOCKETS WITH RED LED				
Angular ± 3°	Date 03/06/19	Drawing Number APP-001-20AMP			