

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0191640048](#)
Status: **Active**
Overview: [Perma-Seal™ Terminals](#)
Description: Perma-Seal™ Male Quick Disconnect Tab for 14-16 AWG Wire, Tab Size 6.35 x 0.81mm

Documents:
[3D Model](#)
[Drawing \(PDF\)](#)
[Product Specification PS-19902-011-001 \(PDF\)](#)
[Product Specification PS-19902-013-001 \(PDF\)](#)
[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

CSA LR18689
UL E79133

General

Product Family Quick Disconnects
Series [19164](#)
Crimp Quality Equipment Yes
Insulated Fully
Overview [Perma-Seal™ Terminals](#)
Product Name Perma-Seal™
Type Quick Disconnect
UPC 800753113336

Physical

Barrel Type Closed
Color - Resin Blue
Gender Male
Glow-Wire Compliant No
Insulation NiAc™
Lock to Mating Part None
Material - Metal Brass
Material - Plating Mating Zinc Chromate
Material - Plating Termination Zinc Chromate
Material - Resin Nylon
Net Weight 1.724/g
Orientation Straight
Packaging Type Bag
Plating min - Mating 5.080µm
Plating min - Termination 5.080µm
Tab Thickness 0.81mm
Tab Width 6.35mm
Temperature Range - Operating -55°C to +125°C
Wire Insulation Diameter 4.32mm max.
Wire Size AWG 14, 16
Wire Size mm² 1.00-2.50

Electrical


Voltage - Maximum 600V

Material Info

Engineering Number SBB-9262

Reference - Drawing Numbers

Product Specification PS-19902-011-001, PS-19902-013-001
Sales Drawing SD-19164-039



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per
-ED/79/2015 (17
December 2015)

Halogen-Free

Status

Low-Halogen

**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

[19164 Series](#)

This document was generated on 08/24/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION