

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0780013344](#)
Status: **Active**
Overview: [MiniDIMM Sockets](#)
Description: 0.60mm Pitch miniDIMM DDR3 Socket, Surface Mount, Reverse Right Angle, with Off-White Latches, 1.5V Voltage Key, 244 Circuits, Type B Tray Packaging, Lead-Free

Documents:
[3D Model](#) [Application Specification AS-87782-001-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [Packaging Specification PK-78001-003 \(PDF\)](#)
[Product Specification PS-78001-001-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)


Agency Certification
CSA LR19980
UL E29179

General
Product Family Memory Module Sockets
Series [78001](#)
Application Tooling Part Link 62100-1900
Application Tooling Part Link 62100-1950
Component Type Socket
Electrical Model Yes
JEDEC Outline MO-244
Overview [MiniDIMM Sockets](#)
Product Name MiniDIMM
UPC 883906425890

Physical
Circuits (Loaded) 244
Durability (mating cycles max) 25
Entry Angle 90° Angle (Side Entry)
Flammability 94V-0
Housing Color Black
Keying to Mating Part Yes
Latch Color Natural (Off-White)
Material - Metal Copper Alloy
Material - Plating Mating Gold
Material - Plating Termination Tin
Material - Resin High Temperature Thermoplastic
Net Weight 10.166/g
PCB Locator Yes
PCB Retention Yes
Packaging Type Tray
Pitch - Mating Interface 0.60mm
Plating min - Mating 0.762µm
Plating min - Termination 2.540µm
Temperature Range - Operating -55°C to +85°C
Termination Interface: Style Surface Mount

Electrical
Current - Maximum per Contact 1.0A
Voltage - Maximum 30V
Voltage Key 1.5V

Solder Process Data
Duration at Max. Process Temperature (seconds) 005
Lead-freeProcess Capability REFLOW
Max. Cycles at Max. Process Temperature 002



Series image - Reference only

EU ELV
Not Relevant

EU RoHS **China RoHS**
Compliant
REACH SVHC
Not Contained Per -
ED/30/2017 (7 July
2017)
Halogen-Free
Status
Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS Green Image
ELV Not Relevant
RoHS Phthalates Not Contained

Search Parts in this Series
[78001](#) Series

Mates With
JEDEC MO-258 Modules

Process Temperature max. C	260
Material Info	
Reference - Drawing Numbers	
Application Specification	AS-87782-001-001
Electrical Model Document	EE-78001-001
Packaging Specification	PK-78001-003
Product Specification	PS-78001-001-001
S-Parameter Model	SP-78001-001
Sales Drawing	SD-78001-003

This document was generated on 08/03/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION