

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0755860009

Status:


Active

Overview:

iPass™ Connector System

Description:

0.80mm Pitch, iPass™ I/O Surface Mount Receptacle, Right Angle, External Application, 26 Circuit, 0.76µm Gold (Au)



Series image - Reference only

|                                                                |                                                                  |
|----------------------------------------------------------------|------------------------------------------------------------------|
| Documents:                                                     |                                                                  |
| <a href="#">3D Model</a>                                       | <a href="#">Application Specification AS-75586-001-001 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>                                  | <a href="#">Packaging Specification PK-75586-002 (PDF)</a>       |
| <a href="#">Product Specification PS-75586-001-001 (PDF)</a>   | <a href="#">Packaging Specification PK-75586-101 (PDF)</a>       |
| <a href="#">Application Specification AS-170432-0003 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>             |

|                                |                                       |
|--------------------------------|---------------------------------------|
| Agency Certification           |                                       |
| CSA                            | LR19980                               |
| UL                             | E29179                                |
| General                        |                                       |
| Product Family                 | I/O Connectors                        |
| Series                         | 75586                                 |
| Application                    | Wire-to-Board                         |
| Component Type                 | Receptacle                            |
| Electrical Model               | Yes                                   |
| MolexKits                      | Yes                                   |
| Overview                       | iPass™ Connector System               |
| Product Name                   | iPass™, Mini Multi-Lane, PCI Express* |
| Type                           | N/A                                   |
| UPC                            | 822348849543                          |
| Physical                       |                                       |
| Boot Color                     | N/A                                   |
| Circuits (Loaded)              | 26                                    |
| Circuits (maximum)             | 26                                    |
| Color - Resin                  | Black                                 |
| Durability (mating cycles max) | 250                                   |
| Flammability                   | 94V-0                                 |
| Gender                         | Female                                |
| Keying to Mating Part          | None                                  |
| Lock to Mating Part            | None                                  |
| Material - Metal               | High Performance Alloy (HPA)          |
| Material - Plating Mating      | Gold                                  |
| Material - Plating Termination | Tin                                   |
| Material - Resin               | High Temperature Thermoplastic        |
| Net Weight                     | 0.723/g                               |
| Number of Rows                 | 2                                     |
| Orientation                    | Right Angle                           |
| PCB Locator                    | Yes                                   |
| PCB Retention                  | None                                  |
| PCB Thickness - Recommended    | 1.35mm                                |
| Packaging Type                 | Embossed Tape on Reel                 |
| Panel Mount                    | No                                    |
| Pitch - Mating Interface       | 0.80mm                                |
| Pitch - Termination Interface  | 0.80mm                                |
| Plating min - Mating           | 0.762µm                               |
| Plating min - Termination      | 2.540µm                               |
| Polarized to Mating Part       | Yes                                   |
| Polarized to PCB               | Yes                                   |
| Ports                          | 1                                     |

EU ELV

Compliant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per - ED/30/2017 (7 July 2017)

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

Green Image

ELV

Compliant

RoHS Phthalates

Not Contained

Search Parts in this Series

75586 Series

Mates With

74547 iPass™ Cable Assembly

Use With

74548 I/O Connectors

|                                |                |
|--------------------------------|----------------|
| Surface Mount Compatible (SMC) | Yes            |
| Temperature Range - Operating  | -40°C to +80°C |
| Termination Interface: Style   | Surface Mount  |
| Waterproof / Dustproof         | No             |
| Wire Insulation Diameter       | N/A            |
| Wire Size AWG                  | N/A            |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.5A            |
| Grounding to Panel            | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Solder Process Data**

|                                                |        |
|------------------------------------------------|--------|
| Duration at Max. Process Temperature (seconds) | 020    |
| Lead-freeProcess Capability                    | REFLOW |
| Max. Cycles at Max. Process Temperature        | 001    |
| Process Temperature max. C                     | 260    |

**Material Info**

**Reference - Drawing Numbers**

|                           |                                  |
|---------------------------|----------------------------------|
| Application Specification | AS-170432-0003, AS-75586-001-001 |
| Electrical Model Document | EE-75586-001                     |
| Packaging Specification   | PK-75586-002, PK-75586-101       |
| Product Specification     | PS-75586-001-001                 |
| S-Parameter Model         | SP-75586-001                     |
| Sales Drawing             | SD-75586-001                     |

\*PCI Express is a registered trademark of PCI-SIG®.

This document was generated on 08/29/2017

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**