

http://www.molexkits.com

Datasheet for 76650-0031

General Information

Kit Part Number: 76650-0031

Connector Type: Solderless Terminals

Solution: Maintenance, Repair and Operation Connectors

Molex Family: Solderless Terminals

Certificates: N/A

Country of Origin: Kit assembled in U.S.A

Specifications

Insulation: Non-Insulated, PVC

Mounting Style: Non-Mounted

Orientation: Assorted Quick Disconnect Terminals

Product/Type: Assorted Terminals

Stud/Tab Size: # 10, # 6, .250" (6.35mm)

Tool Included: Yes

Wire Gauge (AWG): 16-14, 22-18

Product Hightlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade. Spades have the open tongue end used for rapid insertion on the mounting screw. The spade is usually used on free standing studs. Butt Splices allow two stripped wires to be inserted into each end and "butt" in the center, with the crimp securing both wires together.

Features and Benefits

- Terminals employ the full barrel length that eliminates costly and time consuming location when crimping
- Finest quality electrolytic copper
- One-piece design, butted seam
- \bullet The Spades open tongue end is for rapid insertion on the mounting screw / stud
- The basic Ring Tongue type is the safest and most reliable because it cannot be disconnected unless the screw is completely removed.
- Block Spades are designed for use in terminal blocks

Applications

- MRO (Maintenance Repair and Operations)
- Consumer Applications
- Power Applications
- Motor Applications
- Powertrains
- Transportation
- Construction / Mining
- Energy / Power
- Production Equipment
- Instrumentation
- Environmental Equipment and Controls
- Blower Motors



http://www.molexkits.com

| Bill of Materials | | | |
|-------------------|--|----------|--|
| Molex Part No. | Description | Quantity | |
| 19017-0037 | Insulated 6.35mm (.250") Female Quick Disconnect Terminal, 16-14 AWG | 40 | |
| 19023-0012 | Insulated 6.35mm (.250") Male Quick Disconnect Terminal, 16-14 AWG | 40 | |
| 19054-0035 | Insulated #6 Ring Tongue Terminal, 22-18 AWG | 40 | |
| 19054-0039 | Insulated #10 Ring Tongue Terminal, 22-18 AWG | 40 | |
| 19054-0081 | Insulated #6 Ring Tongue Terminal, 16-14 AWG | 40 | |
| 19054-0113 | Insulated #10 Ring Tongue Terminal, 16-14 AWG | 40 | |
| 19119-0004 | Insulated #6 Flanged Block Spade Terminal, 22-18 AWG | 40 | |
| 19130-0044 | Insulated #6 Block Spade Terminal, 16-14 AWG | 40 | |
| 19130-0046 | Insulated #10 Block Spade Terminal, 16-14 AWG | 40 | |
| 19154-0004 | Insulated Butt Splice Connector, 22-18 AWG | 40 | |
| 19154-0015 | Insulated Butt Splice Connector, 16-14 AWG | 40 | |
| 19160-0002 | Insulated Nylon Closed-end Connector, 16-14 AWG | 40 | |
| CT-4071-1R | Universal Hand Crimpping Tool, 22-10 AWG | 1 | |

| Recommended Molex Tool | | | |
|----------------------------------|---------------------------|--|--|
| Molex Part No. | Descripition | | |
| CT-4071-1R (included in kit) | No Additional Information | | |
| 64001-0100 (not included in kit) | Click for more info | | |