

http://www.molexkits.com

Datasheet for 76650-0034

General Information

76650-0034

Kit Part Number: **Connector Type:**

Solderless Terminals

Solution:

Maintenance, Repair and Operation Connectors

Molex Family:

Solderless Terminals

Certificates:

N/A

Country of Origin:

Kit assembled in U.S.A

Specifications

Insulation:

Non-Insulated

Mounting Style:

Non-Mounted

Orientation:

Assorted .250" Tab Quick Disconnect Terminals

Product/Type:

.250" Tab Quick Disconnects

Stud/Tab Size:

.250" Tabs

Tool Included:

No

Wire Gauge (AWG):

12-10, 16-14, 22-18

Product Hightlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Features and Benefits

- Terminals employ the full barrel length that eliminates costly and time consuming location when crimping
- Finest quality electrolytic copper
- One-piece design, butted seam

Applications

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications
- Powertrains
- Transportation
- Construction / Mining
- Energy / Power
- Production Equipment
- Instrumentation
- Environmental
- Equipment and Controls
- Blower Motors



http://www.molexkits.com

Bill of Materials		
Molex Part No.	Description	Quantity
19016-0009	Non-insulated 6.35mm (.250") Female Quick Disconnect Terminal, 22-18 AWG	25
19016-0069	Non-insulated 6.35mm (.250") Female Quick Disconnect, 12-10 AWG	25
19022-0004	Non-insulated 6.35mm (.250") Male Quick Disconnect Terminal, 22-18 AWG	25
19022-0015	Non-insulated 6.35mm (.250") Male Quick Disconnect Terminal, 12-10 AWG	25
19022-0018	Non-insulated 6.35mm (.250") Male Quick Disconnect Terminal, 16-14 AWG	25
19016-0111	Non-insulated 6.35mm (.250") Female Quick Disconnect Terminal, 16-14 AWG	25

Recommended Molex Tool		
Molex Part No.	Descripition	
64003-1100 (not included in kit)	Click for more info	
64003-1100 (not included in kit)	Click for more info	