

Honeywell Sensing and Control

Search



narrow your search

Products

- Controls Monitoring and Lighting (352)
- Machine Safety (1701)
- Sensors (6224)
- Switches (9749)
- Wireless (39)

Technology

- Control and Instrumentation (1052)
- Electromechanical (9301)
- Magnetic (541)
- Optical/Infrared (1042)
- Thick Film (1764)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPM
XYR6000™

[find out more](#)

white papers

Wireless Switches Offer
Unlimited Benefit
Basic Switches Are Not Created
Equal
Applying Precision Switches
Sensors for Medical Devices
New Ways to Measure Torque
Choosing Safety Switches
Specifying Hour Meters

Need help?

[Click here to contact us](#)

16CX1C

(Home : Products : Switches » MICRO SWITCH™ Hazardous Location Switches » CX)



Lever NOT included

Actual product appearance
may vary.
[click here to download Hi-Res image](#)

Explosion-Proof Limit Switches Series CX: Short Housing: Side Rotary; Lever not included

[Sales & Service](#)[Distributor Inventory](#)

[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Availability	Global
Operating Force (OF)	1,25 Nm [.922 lb ft] max.
Release Force	0,113 Nm [.083 lb ft] min.
Pretravel (PT)	30° max.
Overtravel (OT)	75° min.
Differential Travel (DT)	20° max.
Product Type	MICRO SWITCH™ Weather-Sealed, Explosion-Proof Limit Switches
Actuator	Side Rotary
Lever Type	Lever Not Included - Reference Lever Required Accessory
Circuitry	1NC 1NO SPDT Snap Action; Maintained; 1 Basic Switch
Ampere Rating	1 A Ind.
Supply Voltage	120 Vac
Housing Material	Aluminum
Termination Type	0.75 in - 14NPT Conduit
Housing Type	CX: Short: 104 mm [4.09 in]
Series Name	CX
Sealing	NEMA 1, 3, 4, 4x, 6, 6P, 7 (Class I, Division 1, Groups B, C, D), 9 (Class II, Division 1, Groups E, F, G), 13
CSA File #	LR57324
UL File #	E14274
Operating Temperature	-40 °C to 85 °C [-40 °F to 185 °F]
Comment	Switch element hermetic sealed; Low temperature construction
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof

contacts

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



my links

Login to iCOM
Login to Rep/AD Portal
Login to Digital University

News Center

HONEYWELL ANNOUNCES
ADDITION TO RELIALIGN™
RESIDENTIAL DOOR
INTERLOCK SWITCHES THAT
FEATURE RUGGED, PLASTIC
HOUSING

HONEYWELL RELEASES
UNLIMITED POTENTIAL WITH
NEW LIMITLESS™ WIRELESS
SWITCHES

HONEYWELL'S XYR6000
WIRELESS POSITION SENSOR
ENABLES MONITORING IN
HAZARDOUS AREAS AND
REMOTE LOCATIONS

**MICRO SWITCH
Anniversary site**