# Honeywell


KEY INDUSTRIES SERVED

PRODUCTS & INFORMATION

NEWS & EVENTS

→ Honeywell.com → Automation & Control Solutions

LOG





#### narrow your search

#### Products

- Controls Monitoring and
- Lighting (286)
- Machine Safety (1727) Sensors (6158)

- Switches (9781) Wireless (45)

## Technology

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...

### new products

#### **New Wireless Products**

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

#### white papers

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created

Applying Precision Switches Sensors for Medical Devices

New Ways to Measure Torque

Choosing Safety Switches

Specifying Hour Meters

#### Need help?

Click here to contact us

( Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TL )

Documentation



TL Series Toggle Switch, 4 pole, 3 position, Screw terminal, Standard Lever

Actual product appearance may

Overview

Sales & Service 2

Application Notes

Opposite

Distributor Inventory 2

Technical Support

SALES & SUPPORT

Global Sales & Service

View Site Demo Site Comments?

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



# my links

Login to iCOM Login to Rep/AD Portal Login to Digital University

# **News Center**

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITs TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

> MICRO SWITCH Anniversary site

#### **Product Specifications**

Specs

Circuitry/Operating action

Center Maintained Maintained Keyway Position Position 11 10 12 11

MICRO SWITCH™ Toggle Switch Product Type

Ampere/Voltage Range (Resistive Load) 0.5~A to 20 A at 0.5 Vdc to 28 Vdc,0.75 A at 115 Vdc,0.5 A to 15 A at 0.5 Vac to 277 Vac,0.5 A at 250 Vdc

4PDT

Action 3 position Mounting Bushing 15/32 in Termination Screw

Lever Type Standard Comment Silver cadmium oxide contacts

Availability Global

UNSPSC Code 30211908

UNSPSC Commodity 30211908 Toggle switches Series Name

Circuitry

Terms & Conditions | Privacy Statement | Site Map

16/07/2011 09:45 1 of 1