Honeywell

ABOUT US

KEY INDUSTRIES SERVED

PRODUCTS & INFORMATION

NEWS & EVENTS

→ Honeywell.com → Automation & Control Solutions

SALES & SUPPORT

Technical Support

View Site Demo

Site Comments?

Global Sales & Service

LOG



narrow your search

Products

- Controls Monitoring and
- Lighting (286) Machine Safety (1727)
- Sensors (6158)

- Switches (9781) Wireless (45)

Technology

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created

Applying Precision Switches

Sensors for Medical Devices

New Ways to Measure Torque

Choosing Safety Switches Specifying Hour Meters

Need help?

Click here to contact us

(Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TL)

Documentation



TL Series Toggle Switch, 4 pole, 3 position, Screw terminal, Standard Lever

Actual product appearance may

Overview

Application Notes

Sales & Service 3

Distributor Inventory 2

meet dr. larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.





my links

Login to iCOM Login to Rep/AD Portal Login to Digital University

News Center

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITs TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

> MICRO SWITCH Anniversary site

Product Specifications

Specs

Circuitry/Operating action

Keyway Opposite Keyway **Momentary Center** Position Position Position ON

Product Type MICRO SWITCH™ Toggle Switch

Ampere/Voltage Range (Resistive Load)

0.75 A at 115 Vdc,0.5 A to 18 A at 0.5 Vdc to 28 Vdc,0.5 A to 10 A at 0.5 Vac to 277

Vac, 0.5 A at 250 Vdc

Circuitry Action 3 position Mounting Bushing 15/32 in

Termination Screw Lever Type

Comment Silver cadmium oxide contacts

Availability Global UNSPSC Code 30211908

UNSPSC Commodity 30211908 Toggle switches

Series Name

Terms & Conditions | Privacy Statement | Site Map

16/07/2011 09:48 1 of 1