Honeywell

KEY INDUSTRIES SERVED

PRODUCTS & INFORMATION

NEWS & EVENTS

→ Honeywell.com → Automation & Control Solutions

SALES & SUPPORT

Customer Service

Technical Support

View Site Demo

Site Comments?

Global Sales & Service

LOG



narrow your search

Products

- Controls Monitoring and
- Lighting (286) Machine Safety (1727)
- Sensors (6158)
- Switches (9781) Wireless (45)

Technology

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created

Applying Precision Switches

Sensors for Medical Devices

New Ways to Measure Torque Choosing Safety Switches

Specifying Hour Meters

Need help?

Click here to contact us

(Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TL)

Documentation



TL Series Toggle Switch, 4 pole, 2 position, Screw terminal, Standard Lever

Actual product appearance may

Overview

Sales & Service 2

Application Notes

Distributor Inventory 2

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



meet dr. larry

my links

Login to iCOM Login to Rep/AD Portal Login to Digital University

News Center

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITs TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

> MICRO SWITCH Anniversary site

Product Specifications

Specs

Circuitry/Operating action

Opposite Maintained Maintained Keyway Keyway Position Position 10 12 12 11 11 ON ON

MICRO SWITCH™ Toggle Switch Product Type

Standard

Ampere/Voltage Range

0.75 A at 115 Vdc,0.5 A to 10 A at 0.5 Vac to 277 Vac,0.5 A to 18 A at 0.5 Vdc to 28

Vdc,0.5 A at 250 Vdc (Resistive Load)

Circuitry 4PDT 2 position Action Mounting Bushing 15/32 in Termination Screw

Lever Type Comment Silver cadmium oxide contacts

Availability Global UNSPSC Code 30211908

UNSPSC Commodity 30211908 Toggle switches

Series Name

Terms & Conditions | Privacy Statement | Site Map

16/07/2011 09:54 1 of 1