ABOUT US

KEY INDUSTRIES SERVED PRODUCTS & INFORMATION NEWS & EVENTS

→ Honeywell.com → Automation & Control Solutions

SALES & SUPPORT

Technical Support

View Site Demo

Site Comments?

VIDEO - Dr. Larry Goldstein explains out

Global Sales & Service

LOG

contacts

Honeywell Sensing and Control



narrow your search Products

- Controls Monitoring and Lighting (286)
- Machine Safety (1727)
- Sensors (6158)
- Switches (9781)
- Wireless (45)

Technology

- Control and Instrumentation (890)
- Electromechanical (9303)
- Magnetic (538)
- Platinum thin film (56)
- Thick Film (1372)
- More...

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site WGLA and WPMM XYR6000™

find out more

white papers

Wireless Switches Offer Unlimited Benefit

Basic Switches Are Not Created

Applying Precision Switches

Sensors for Medical Devices


New Ways to Measure Torque

Choosing Safety Switches Specifying Hour Meters

Need help?

Click here to contact us

(Home : Products : Switches » MICRO SWITCH™ Rocker Switches » Power-duty Rocker Switches » TP)



TP Series Rocker Switch, 4 pole, 3 position, Screw terminal, Flush Panel Mounting

Sales & Service 3

Actual product appea may vary

Application Notes

Distributor Inventory 2

technologies.

newest and best Meet Dr. Larry



meet dr. larry

my links

Login to iCOM Login to Rep/AD Portal Login to Digital University

News Center

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

HONEYWELL EXPANDS ITS LIMITLESS™ PLATFORM WITH THE LAUNCH OF ITS GLOBALLY AVAILABLE INDUSTRIAL WIRELESS RECEIVER

HONEYWELL EXTENDS ITs TRUSTABILITY® PRESSURE SENSOR PRODUCT LINE WITH A SINGLE SIDE LIQUID MEDIA OPTION

> MICRO SWITCH Anniversary site

Product Specifications

Overview


action

MICRO SWITCH™ Rocker Product Type Contact Type Silver Cadmium Oxide Contacts 4PDT Circuitry

Documentation

3 position Action Circuitry/Operating

Specs



Mounting Flush Panel Lamp Type Transparent Termination

Ampere/Voltage Range 0.5 A at 250 Vdc.0.75 A at 115 Vdc.0.5 A to 20 A at 0.5 Vdc to 28 Vdc.0.5 A to 15 A at (Resistive Load)

LED/Lamp/Neon Voltage L191: 15 A-125, 250, 277 Vac; 1/2 Hp-125 Vac; 1 Hp-250, 277 Vac; 5 A-120 Vac "L"

Comment Silver cadmium oxide contacts

Availability Global UNSPSC Code 302119

UNSPSC Commodity 302119 Switches and controls and relays

Series Name

Terms & Conditions | Privacy Statement | Site Map

16/07/2011 10:03 1 of 1