



MICRO SWITCH
FREEPORT ILLINOIS U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

SWITCH-ENCLOSED

CATALOG LISTING
602EN99-B

CIRCUIT DIAGRAM



.072 ±.004 WIDE X .031 ±.003 KEYWAY
TO WITHIN .250 OF SHOULDER

CORROSION RESISTANT STEEL PLUNGER AND BUSHING

15/32-32 UNS-2A THREAD TO WITHIN .090 OF SHOULDER

CORROSION RESISTANT STEEL HEX NUT,
.62 ACROSS FLATS X .125 THICK

2X NO.20 WIRE LEAD PER MIL-W-22759/11 MARKED WITH
CIRCUIT IDENTIFICATION AND WIRE GAGE (1-20 AND 2-20) PER
MIL-W-5088

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY
OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT
TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

SCALE FULL

DO NOT SCALE PRINT

TOLERANCES
APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR
REFERENCE. UNLESS NOTED, TOLERANCES ARE:

	DIM.	TOL.	DIM.	TOL.
	mm	mm/in	in	mm/in
NO PLACES	X	1/64	X	0.015
ONE PLACE	X, X	0.001	X, X	0.001
TWO PLACES	X, X, X	0.0005	X, X, X	0.0005
THREE PLACES	X, X, X, X	0.0001	X, X, X, X	0.0001
ANGLES				

DESIGN UNITS

SI METRIC ☐ US CUSTOMARY ☒

RAW MATERIAL-COMMERCIAL STANDARD
MICRO SWITCH STANDARDS APPLY
DIMENSIONS ARE TO BE MET BEFORE
PROTECTIVE COATINGS ARE APPLIED

WEIGHT 2.5 OZ MAX

NOTES

- 1 - CORROSION RESISTANT STEEL ENCLOSURE
- 2 - SWITCH SEALED PER MIL-PRF-8805 SYMBOL 4
- 3 - CIRCUIT DIAGRAM, DATE CODE, FED. MFG. CODE
AND CAT. LIST. ARE SHOWN ON NAMEPLATE
- 4 - NOTED ELECTRICAL RATINGS APPLY AS SPECIFIED IN
MIL-PRF-8805/43 UP TO 185°F
- 5 - HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-PRF-8805
- 6 - THIS DIMENSION EXCLUDES THE RESILIENT POTTING MATERIAL
ON THE BOTTOM OF THE SWITCH

ANSI Y14.5M-1982 APPLIES

602EN99-B

PAGE 1 OF 1

M

DRAWING
NUMBER

ISSUE

13

12

11

REVISIONS

A CO

44351

S L B

4 MAR 80

B CO47573

J A P

7 AUG 80

C CO

49280

J M J

25 MAR 81

D CO-56280

J A S

31 OCT 84

E CO

60123

S J S

24 SEP 86

F CO94274

DLM

17 MAR 99

FORMTEK
FO-52851-A

DRAWN

S L B 4 MAR 80

C E B 5 MAR 80