




FED. MFG. CODE 91929

CATALOG LISTING
604HE224-RB

CATALOG LISTING



CIRCUIT DIAGRAM



CHARACTERISTICS	
OPERATING FORCE	— — — — 5 –12 LB
FULL OVERTRAVEL FORCE	— — — — 30 LB MAX
RELEASE FORCE	— — — — — 3 LB MIN
PRETRAVEL	— — — — — .040 MAX
DIFFERENTIAL TRAVEL	— — — — — .020 MAX
OVERTRAVEL	— — — — — .125 MIN

	CONTACT ARRANGEMENT
	4X S P D T

LOAD	28 VDC
	SEA LEVEL & 100,000 FT.
RES	1
IND	0.5
MOTOR	

DO NOT SCALE PRINT

ONE PLACE	(.0)	$\pm .030$
TWO PLACE	(.00)	$\pm .015$
THREE PLACE	(.000)	$\pm .005$
ANGLES		$\pm$

WEIGHT

- 1 - CORROSION RESISTANT STEEL ENCLOSURE
- 2 - SWITCH SEALED PER MIL-S-8805 SYMBOL 5
- 3 - COINCIDENCE OF OPERATING AND RELEASING POINTS: .010 INCH OF PLUNGER TRAVEL
- 4 - CIRCUIT DIAGRAM, AND CATALOG LISTING SHOWN ON NAMEPLATE
- 5 - REPLACEMENT MOUNTING HARDWARE - PACKET 19PA9
- 6 - FOR OPERATION IN TEMPERATURE OF MINUS 65°F TO PLUS 257°F
- 7 - HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-S-8805

ANSI Y14.5M-1982 APPLIES