


[→ Honeywell.com](#) [→ Automation & Control Solutions](#)
[HOME](#)
[ABOUT US](#)
[KEY INDUSTRIES SERVED](#)
[PRODUCTS & INFORMATION](#)
[NEWS & EVENTS](#)
[SALES & SUPPORT](#)
[LOG](#)

Honeywell Sensing and Control

Search


11TW1-5M

(Home : Products : Switches » MICRO SWITCH™ Toggle Switches » TW)

narrow your search

Products

- Controls and Monitoring (280)
- Machine Safety (1566)
- Sensors (5798)
- Switches (9572)
- Wireless (45)

Technology

- Electromechanical (9255)
- Magnetic (530)
- Optical/Infrared (1019)
- Platinum thin film (56)
- Thick Film (1309)
- More...



Actual product appearance may vary.

TW Series Toggle Switch, 1 pole, 3 position, Solder terminal, Locking Lever, Military Part Number MS27720-31-1M

[Sales & Service](#)
[Distributor Inventory](#)

contacts

Customer Service
Technical Support
Global Sales & Service
View Site Demo
Site Comments?

Meet Dr. Larry

VIDEO - Dr. Larry Goldstein explains our newest and best technologies.

Meet Dr. Larry



My Links

Login to eCOM
Login to Rep/AD Portal
Login to Digital University

News Center

HONEYWELL LAUNCHES WATERTIGHT MINIATURE SWITCHES

HONEYWELL INTRODUCES NEW HUMIDICON™ DIGITAL HUMIDITY/TEMPERATURE SENSORS

HONEYWELL EXPANDS INDUSTRY-LEADING TRUSTABILITY® PLATFORM WITH NEW BOARD MOUNT ULTRA-LOW PRESSURE SENSORS

HONEYWELL INTRODUCES TRUSTABILITY® NSC SERIES, UNCOMPENSATED / UNAMPLIFIED BOARD MOUNT PRESSURE SENSORS

MICRO SWITCH Anniversary site

new products

New Wireless Products

Go farther. Work smarter. Explore new possibilities. Just by cutting the cord and making the switch.



Wireless Web Site
WGLA and WPMM
XYR6000™

[find out more](#)

White Papers

Wireless Switches Offer Unlimited Benefit
Basic Switches Are Not Created Equal
Applying Precision Switches
Sensors for Medical Devices
New Ways to Measure Torque
Choosing Safety Switches
Specifying Hour Meters


Need Help?

[Click here to contact us](#)

[Overview](#) [Specs](#) [Documentation](#) [Application Notes](#)

Product Specifications

Circuitry/Operating action



MICRO SWITCH™ Toggle Switch



Locked out of and into extreme position (Opposite keyway)

Product Type
Lever Lock

Ampere/Voltage Range (Resistive Load)	0.1 A to 5.0 A at 0.5 Vac to 115 Vac, 0.1 A to 5.0 A at 0.5 Vdc to 28 Vdc
Circuitry	SPDT
Action	3 position
Mounting	Bushing 15/32 in
Termination	Solder
MIL Spec. Number	MS27720-31-1M
Lever Type	Locking
UL/CSA	L117: 5 A at 125 Vac
Comment	Fine silver contacts
Availability	Global
UNSPSC Code	30211908
UNSPSC Commodity	30211908 Toggle switches
Series Name	TW

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)