

LSXYAB3K

(Home : Products : basics : Switches : MICRO SWITCH™ Hazardous Location Switches : LSX)



Explosion-Proof Limit Switches LSX Non Plug-in: Low Temperature Version; Side Rotary; 1NC 1NO SPDT Snap Action; 0.5 in - 14NPT conduit

Lever NOT included

Actual product appearance may vary.

Sales & Service

Distributor Inventory

Overview **Specs** Documentation Application Notes

Product Specifications	
Availability	Global
Operating Force (OF)	0,45 Nm [4 in lb] max.
Pretravel (PT)	15° max.
Overtravel (OT)	60° min.
Differential Travel (DT)	5° max.
Product Type	MICRO SWITCH™ Weather-Sealed, Explosion-Proof Limit Switches
Actuator	Side Rotary
Lever Type	Lever Not Included - Reference Lever Required Accessory
Circuitry	1NC 1NO SPDT Snap Action, Double-Break
Ampere Rating	10 A (Thermal)
Supply Voltage	600 Vac and 250 Vdc max.
Housing Material	Zinc Die-Cast
Termination Type	0.5 in - 14NPT Conduit
Housing Type	LSX Non Plug-in
Series Name	LSX
Sealing	NEMA 1, 3, 4, 6, 7 (Class 1, Division 1, Groups B, C, D), 9 (Class 2, Division 1, Groups E, F, G), 13
CSA File #	LR57327
UL File #	E61730
Operating Temperature	-40 °C to 121 °C [-40 °F to 250 °F]
Comment	Low Temperature Construction
Agency Approvals and Standards	UL, CSA
UNSPSC Code	302119
UNSPSC Commodity	302119 Switches and controls and relays
Sealed	Explosion-proof

Distributor Inventory

Input part number for stock availability

Narrow Your Search

Modify Your Search

Products

Select Option

Technology

Select Option

Industries Served

Select Option

Product Search

Product Type:

Industry:

Search Term:

- New Products Only
- Entire Product Catalog

Search

My Links

- [eCOM Login](#)
- [Request Access to eCOM](#)
- [Rep/AD Portal Login](#)
- [Rep/AD Portal Access Request](#)
- [Sample Request](#)
- [Digital University Login](#)
- [Limitless Microsite](#)
- [Supplier Microsite](#)

Literature and Media

- [Application Demos](#)
- [White Papers](#)
- [Application Notes](#)
- [Literature Request](#)
- [Data Sheets](#)
- [Videos](#)

Contacts

- [Customer Service](#)
- [Technical Support](#)
- [Global Sales & Service](#)
- [Website Feedback](#)



[Terms & Conditions](#)

[Privacy Statement](#)

[Site Map](#)